

CONTENT

PAPERS

<b>Estimation of Modal Decay Parameters from Noisy Response Measurements</b> .....Matti Karjalainen, Poju Antsalu, Aki Mäkivirta, Timo Peltonen, and Vesa Välimäki	867
<i>Estimating decay parameters, such as room reverberation or string decay of musical instruments, becomes more inaccurate as the noise level increases if that noise is not also included in the parametric model. A new method based on nonlinear optimization of a linear model with additive noise is demonstrated as being more accurate than the traditional approaches, especially at extreme noise conditions. Several practical examples illustrate the utility of the proposed method.</i>	
<b>On the Use of Time–Frequency Reassignment in Additive Sound Modeling</b> .....Kelly Fitz and Lippold Haken	879
<i>The conventional short-time spectral analysis is unable to parameterize signals that have both narrow-band components combined with transients because of the nature of the time–frequency definition. Moreover, a single musical partial, which often has time-varying amplitude and frequency envelopes, does not appear as a single component in the classical linear analysis approach. By reassigning energy components, temporal smear is greatly reduced because unreliable data points can be removed from the representation. Several examples illustrate the ability to reconstruct abrupt onset square waves.</i>	
<b>Scalable Multichannel Coding with HRFT Enhancement for DVD and Virtual Sound Systems</b> .....M. O. J. Hawksford	894
<i>Using the perceptual properties embedded in the head-related transfer functions of a normal listener, a standard five- or six-channel audio source can be transformed to feed additional loudspeakers, perhaps as many as 18. The proposed system enhances image stability by optimizing the correct ear signals at the listener’s location. The approach improves spatial resolution over a wider area while retaining backward compatibility with an unprocessed reproduction environment.</i>	
<b>Two-to-Five Channel Sound Processing</b> .....R. Irwan and Ronald M. Aarts	914
<i>In order to reproduce two-channel audio sources in a surround listening environment, the authors evaluated a proposed processing system based on decoding the principle directional component using correlation techniques. By parameterizing direction a stable center channel was created. Moreover, the synthesized ambiance for the sides does not degrade image stability.</i>	

STANDARDS AND INFORMATION DOCUMENTS

<b>AES Standards Committee News</b> .....	927
<i>New Internet facilities; preservation of recordings; storage and handling; audio connectors; grounding and shielding; file exchange</i>	

FEATURES

<b>113th Convention Report, Los Angeles</b> .....	934
<b>Exhibitors</b> .....	950
<b>Program</b> .....	954
<b>Bluetooth and Wireless Networking—A Primer for Audio Engineers</b> .....	979
<b>11th Tokyo Regional Convention, Call for Papers</b> .....	1001

DEPARTMENTS

<b>News of the Sections</b> .....	985	<b>Membership Information</b> .....	993
<b>Sound Track</b> .....	989	<b>Advertiser Internet Directory</b> .....	999
<b>Upcoming Meetings</b> .....	990	<b>In Memoriam</b> .....	1000
<b>New Products and Developments</b> .....	990	<b>Sections Contacts Directory</b> .....	1002
<b>Available Literature</b> .....	992	<b>AES Conventions and Conferences</b> .....	1008