

CONTENTS

PAPERS

- Analysis and Synthesis of Musical Transitions Using the Discrete Short-Time Fourier Transform** John Strawn 3
A study of tone-to-tone transitions was reported in 1986 November. Here, selected uses of the Fourier transform generate resynthesized transitions that are audibly indistinguishable from their originals.
- Mathematical Noise Modeling and Analysis of Some Popular Preamplifier Circuit Topologies** T. F. Darling 15
Analyzing the noise performance of several moving-coil phonograph preamplifiers suggests a preferred circuit.

ENGINEERING REPORTS

- Active RC Crossover Networks with Adjustable Characteristics** Phillip A. Regalia, Nobuo Fujii, Sanjit K. Mitra, and Yrjö Neuvo 24
Two active, tunable crossovers exhibit both constant-amplitude and constant-power network responses.
- A Combined Measurement Method for Both Dynamic Intermodulation and Static Nonlinear Distortions** Paul Skritek 31
A test signal composed of a filtered square wave and high-frequency sinusoid discovers both static and dynamic nonlinearities. Its frequency spectrum and amplitude distribution resemble those of natural signals.
- Linear-Phase Digital Audio Tone Control** Y. C. Lim 38
A relatively simple linear-phase digital filter is proposed to replace the analog tone control.

STANDARDS

- Standards News from JASA** (Reprint, JASA, Vol. 80(5), pp. 1551-1556, 1986 November) 41

FEATURES

- 82nd AES Convention Preview** 50
 Exhibit Previews 52
 Exhibitors 64
- 5th AES International Conference: Music and Digital Technology** 77

DEPARTMENTS

- | | |
|---|--|
| Review of Acoustical Patents 47 | Available Literature 87 |
| News of the Sections 78 | Membership Information 90 |
| Sound Track 84 | Call for Papers—83rd AES |
| Upcoming Meetings 86 | Convention, New York, 1987 93 |
| AES Conventions and Conferences 96 | |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 35 NUMBER 3

1987 MARCH

CONTENTS

PAPERS

The Spectral Recording Process Ray Dolby 99
Signal compression-expansion is inaudible if the large-amplitude frequency components are modulated selectively without affecting component amplitudes in the remainder of the spectrum. Realizing this principle yields a superior method for avoiding distortion and noise in the recording or transmitting channel.

The Acoustics and Sound System for Hemispherical Film Projection Peter H. Heringa, Ben H. M. Kok, and Yves Dekeyrel 119
In a space theater, visual and auditory images must appear to coincide. Systems designed to steer the audio image in range and position have been chosen for theaters in Paris and The Hague.

CD Direct Metal Mastering Technology: A Step Toward a More Efficient Manufacturing Process for Compact Discs Horst Redlich and Günter Joschko 130
Modifications of the direct metal technique for mastering phonograph records make it possible to produce Compact Disc masters by a similar mechanical process.

Production of Spatially Limited "Diffuse" Sound Field in an Anechoic Room Ivar Veit and Harald Sander 138
The random sound field of a reverberation room is simulated in an anechoic environment using an appropriate loudspeaker array and independent signals.

LETTERS TO THE EDITOR

More on "Impulse Measurement of Horn-Type Loudspeaker Drivers" Josef Merhaut 144
Comments on "Another Approach to Time-Delay Spectrometry" Henrik Biering and Ole Z. Pedersen 145
Author's Reply John Vanderkooy 146

STANDARDS

Standards News from JASA (Reprint, JASA, Vol. 81(1), pp. 200-202, 1987 January) 147

FEATURES

5th AES International Conference: Music and Digital Technology—Preliminary Program 154
Personal Computers and Music: The State of the Art Christopher Yavelow 160

DEPARTMENTS

Review of Acoustical Patents	150	Available Literature	200
News of the Sections	194	Membership Information	201
Upcoming Meetings	196	Call for Papers—83rd AES	
Sound Track	196	Convention, New York, 1987	206
New Products and Developments	198	AES Conventions and Conferences	208

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 35 NUMBER 4

1987 APRIL

CONTENTS

PAPERS

- A Boundary-Element Approach to Finite-Element Radiation Problems** Earl Geddes, James Porter, and Yifan Tang 211
With a wise choice of radiation boundary, finite-element analysis of loudspeaker response becomes accurate and efficient.
- A Hybrid Approach to the Variable-Speed Replay of Digital Audio** P. S. Gaskell 230
Digital audio is replayed at speeds from standstill to 20 times normal while low-speed in-band images and high-speed out-of-band components are eliminated.
- Active Realization of Multiway All-Pass Crossover Systems** Joseph A. D'Appolito 239
Any N-way, sum-to-all-pass crossover can be realized as a branched cascade of $N - 1$ two-way, all-pass crossovers with phase-compensating networks.
- A Century of Microphones** B. B. Bauer 246
The technique, beginning in 1860, of using a diaphragm to convert sound waves to electricity is still in flux in 1962.

MESSAGE TO MEMBERS

- Richard C. Heyser (1931-1987) 259

LETTERS TO THE EDITOR

- The Proposed DAT Bill Bart Locanthi 259

FEATURES

- AES 2nd Regional Convention: Advanced Audio Technology for Better Sound** 266
An Early Auditory Training System Samuel F. Lybarger 270

DEPARTMENTS

- | | | | |
|-------------------------------|-----|----------------------------------|-----|
| News of the Sections | 276 | Membership Information | 286 |
| Upcoming Meetings | 280 | Audio Engineering Society Bylaws | 290 |
| Sound Track | 281 | Call for Papers—83rd AES | |
| New Products and Developments | 283 | Convention, New York, 1987 | 294 |
| Available Literature | 285 | AES Conventions and Conferences | 296 |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 35 NUMBER 5

1987 MAY

CONTENTS

PAPERS

Statistical Parameters of the Frequency Response Curves of Large Rooms M. R. Schroeder 299
For a large (irregular) auditorium, theory predicts room-response peaks averaging 10 dB in height and with average frequency separations proportional to the inverse of reverberation time.

Normal Frequency and Excitation Statistics in Rooms: Model Experiments with Electric Waves M. R. Schroeder 307
Room response is studied experimentally with a microwave analog. Randomness of response and excitation requires rooms with only small geometric irregularities or small perturbing structures.

Unified Compressor Measurements by Using a Channel Simulator Paul Skritek 317
Compressor behavior is observed in a channel that is adjustable for bandwidth, frequency response, phase response, frequency-dependent overload and dropouts, and levels of additive and modulation noise and interference.

Editing Time-Varying Spectra John Strawn 337
A large data load must be manipulated in examining and modifying the tone spectra of musical instruments. Shown here are some of the capabilities of an editor devised for short-time Fourier-transform data.

LETTERS TO THE EDITOR

Is Reel-to-Reel Digital Standardization Really Necessary Any More? Stephen F. Temmer 353
Fillbuster Feature Dan Dugan 354

CORRECTIONS

Correction to "Comments on 'Three-Level Tone Test Signal for Setting Audio Levels'" 354

STANDARDS

Standards News from JASA (Reprint, JASA, Vol. 81(3), pp. 800-803, 1987 March) 355

FEATURES

82nd Convention Report 362
 Exhibitors 374
 Program 379
Updates and Additions to 1987 AES International Sections Directory 398

DEPARTMENTS

Educational Directory Update	359	Available Literature	406
News of the Sections	396	Membership Information	407
Sound Track	399	In Memoriam	413
Upcoming Meetings	400	Call for Papers—83rd AES	
Abstracts of Interest	401	Convention, New York, 1987	416
New Products and Developments	402	AES Conventions and Conferences	418

CONTENTS

PAPERS

- Modeling of the Nonlinear Response of an Electrodynamic Loudspeaker by a Volterra Series Expansion** A. J. M. Kaizer 421

An approximate integral equation predicts the nonlinear behavior of a low-frequency driver. Experiment generally confirms the analysis.

- On the Use of Computer-Generated Dithered Test Signals** Robert A. Finger 434

Rigorous measurement (and subjective evaluation) of digital nonlinear distortion may be impossible using nondithered test signals. Dithered signals selected for a test Compact Disc are suggested by experience with dither of different probability densities.

- The Application of Narrow-Band Dither Operating at the Nyquist Frequency in Digital Systems to Provide Improved Signal-to-Noise Ratio over Conventional Dithering** Barry A. Blesser and Bart N. Locanthi 446

Experiment shows that additive narrow-band dither at the Nyquist frequency linearizes the analog-to-digital converter while producing a noise floor lower than is found using additive baseband dither.

- Peak Current Requirement of Commercial Loudspeaker Systems** Matti Ojala and Pertti Huttunen 455

The typical 8-ohm loudspeaker's drivers and crossover networks combine to form reactive terminal impedances of other magnitudes. For a nonsinusoidal worst-case signal, amplifier current may equal that demanded by a 1-ohm resistive load.

ENGINEERING REPORTS

- Reducing Off-Axis Comb-Filter Effects in Highly Directional Microphones** Yuri Shulman 463

Predominantly resistive ports in the tube of a line microphone improve its on-axis and off-axis responses.

LETTERS TO THE EDITOR

- CBS Technology Center: In Memoriam** Emil L. Torick 471

CORRECTIONS

- Correction to "Personal Computers and Music"** 472

FEATURES

- Audio Measurements** Richard C. Cabot 476

MESSAGE TO MEMBERS

- AES Changes in Europe** 506

DEPARTMENTS

- | | |
|---|--|
| Review of Acoustical Patents 473 | New Products and Developments 507 |
| News of the Sections 502 | Available Literature 508 |
| Sound Track 505 | Membership Information 509 |
| Upcoming Meetings 506 | AES Conventions and Conferences 514 |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 35 NUMBER 7/8

1987 JULY/AUGUST

CONTENTS

PAPERS

- Evaluation of the Audible Distortion and Noise Produced by Digital Audio Converters** Louis D. Fielder 517
A measurement technique reveals low-level digital-converter nonlinearities. Distortion resulting from such defects is predictably audible when the masking and critical-band behavior of human hearing is accounted for.
- A High-Performance Surround Sound Process for Home Video** Stephen Julstrom 536
Home-video surround sound is realized with a processor that enhances directional information and delays the signal to the surround loudspeakers.

ENGINEERING REPORTS

- Sound Transmission Through Partitions** Marshall Long
Part 1: Diffuse Source Field 550
Part 2: Direct Source Field 552
Transmission from a source through a partition to a receiving space is analyzed for cases not properly treated by earlier theory.
- Computer Simulation of Horn-Loaded Compression Drivers** Earl Geddes and David Clark 556
Sound pressure, diaphragm displacement, and electrical impedance of a driver and finite horn are calculated using a computer model.

LETTERS TO THE EDITOR

- Comments on "Type 1 and Type 2 Errors in the Statistical Analysis of Listening Tests"**
..... Daniel Shanefield 567
..... David Clark 568
..... Tom Nousaine 568
Author's Reply Les Leventhal 569

TECHNICAL COMMITTEE REPORTS

- Minutes of the Meeting of the AES Standards Subcommittee on Digital Audio** ... Robert A. Finger 573

FEATURES

- 5th International Conference Report** 582
Program 592

DEPARTMENTS

- | | | | |
|--|-----|---|-----|
| News of the Sections | 604 | In Memoriam | 620 |
| Upcoming Meetings | 608 | AES Annual Report | 622 |
| Sound Track | 608 | Call for Papers—84th Convention,
Paris, 1988 | 623 |
| Abstracts of Interest | 610 | Information for Authors of Convention
Papers | 625 |
| New Products and Developments | 611 | AES Conventions and Conferences | 626 |
| Available Literature | 613 | | |
| Membership Information | 615 | | |

CONTENTS

PAPERS

Problems with Shadowless Stereo Theory: Asymptotic Spectral Status	Duane H. Cooper	629
<i>Loudspeaker reproduction of spectrally unmodified stereo microphone signals is audibly unsatisfactory for frequencies above a few hundred hertz. Satisfactory system development is suggested by comparing the findings of J. L. Bauck with other research.</i>		

Complex Simulation of Acoustical Sound Fields by the Delta Stereophony System (DSS)	Wolfgang Ahnert	643
<i>Separated loudspeakers fed with staggered-delay signals provide reinforced sound in several large installations.</i>		

COMMUNICATIONS

The U.K. System for Digital Stereo Sound with Terrestrial Television	S. R. Ely	653
<i>A third carrier, phase-shift keyed at 728 kilobits per second, accommodates two digital sound channels. Laboratory and broadcast tests prove the system ruggedness and compatibility.</i>		

Multichannel Television Sound Broadcasting in the United States	Randy Hoffner	660
<i>Stereophonic audio and two additional subcarrier signals emerge from the system whose history and specifications are given here.</i>		

LETTERS TO THE EDITOR

Comments on "A Psychoacoustically Optimized Loudspeaker"	Malcolm J. Hawksford and Richard Bews	666
Author's Reply	Kenneth L. Kantor	667
Further Corrections on "Design of Optimized Loudspeaker Crossover Networks Using a Personal Computer"	Peter L. Schuck	667

STANDARDS

Standards News from JASA (Reprint, JASA, Vol. 81(5), pp. 1646-1650, 1987 May)		669
--	--	-----

MESSAGE TO MEMBERS

Special Election Results		674
---------------------------------	--	-----

FEATURES

83rd AES Convention Preview		676
Exhibit Previews		678
Exhibitors		718

DEPARTMENTS

News of the Sections	722	Membership Information	731
Upcoming Meetings	728	In Memoriam	741
Sound Track	728	Membership Application Form	742
Available Literature	730	AES Conventions and Conferences	746

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 35 NUMBER 10

1987 OCTOBER

CONTENTS

PAPERS

Three-Dimensional Image Reconstruction in Audio Anthony Romano 749
Sound sources, sufficient in number and suitably placed within a given enclosure, can reproduce a specified sound field. The theory is developed for such reconstruction.

Soft Magnetic Materials for Audio Transformers: History, Production, and Applications G. A. V. Sowter 760
Almost every conceivable audio system now depends on magnetic iron. This history summarizes its development.

Heat-Transfer Mechanisms in Loudspeakers: Analysis, Measurement, and Design Clifford A. Henricksen 778
Temperature rise in a high-power loudspeaker is predicted by analysis of the voice coil's thermal interaction with air, magnet, and loudspeaker frame.

ENGINEERING REPORTS

Electroacoustic System Realizations for the Linkwitz-Riley Crossover Networks W. Marshall Leach, Jr. 792
An active crossover network must include the transfer functions of the higher frequency drivers to produce an overall Linkwitz-Riley response. A simpler network gives approximately similar results.

STANDARDS

Standards News from JASA (Reprint, JASA, Vol. 82(1), pp. 394-399, 1987 July) 801

MESSAGE TO MEMBERS

AES Education Awards 810

FEATURES

2nd Regional Convention Report 812
 Program 820
Review of Society's Sustaining Members 832

DEPARTMENTS

Review of Acoustical Patents	807	Available Literature	857
News of the Sections	851	Membership Information	859
Upcoming Meetings	854	In Memoriam	862
Sound Track	855	Membership Application Form	863
New Products and Developments	856	AES Conventions and Conferences	866

CONTENTS

PAPERS

How to Measure and Interpret Coherence Loss in Magnetic Recording U. Totzek and D. Preis 869
Tape recorder frequency response, distortion, noise, and modulation products are measured by comparing input and output spectra.

Loudspeaker Systems with Optimized Wide-Listening-Area Imaging Mark F. Davis 888
A loudspeaker design method controls directivity to preserve the stereophonic image within a broad listening area.

The Acoustical Design of a 4000-Seat Church A. H. Marshall, C. W. Day, and L. J. Elliott 897
Design of this church auditorium required specification of room acoustics, sound reinforcement, building noise, and isolation from the outside environment.

ENGINEERING REPORTS

Ultra-Low-Noise Amplifiers and Granularity Distortion D. R. G. Self 907
Experiments with a low-noise amplifier reveal none of the microscopic nonlinearities sometimes proposed to explain subjective preference for particular circuit components.

STANDARDS

Standards News from JASA (Reprint, JASA, Vol. 82(3), pp. 1095-1099, 1987 September) 916

FEATURES

Choosing the Right Microphone by Understanding Design Tradeoffs Bruce Bartlett 924

DEPARTMENTS

Data Request for AES Directory of Educational Programs	921	Membership Information	953
News of the Sections	945	Call for Papers—3rd Regional Convention, Melbourne, 1988	956
Upcoming Meetings	948	Information for Authors of Convention Papers	958
Sound Track	948	Membership Application Form	959
New Products and Developments	950	AES Conventions and Conferences	962
Available Literature	952		

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 35 NUMBER 12

1987 DECEMBER

CONTENTS

President's Message	Daniel Gravereaux	965	
PAPERS			
Dither in Digital Audio	John Vanderkooy and Stanley P. Lipshitz	966	
<i>Low-level random noise, added to the audio signal, linearizes digital sampling and improves resolution to less than a sample step. Results are given for different noise spectra.</i>			
Horn Layout Simplified	Bob Thurmond	976	
<i>High-frequency horn positioning is made easier by using linear, equal-level response contours scaled to the auditorium drawings.</i>			
A New Principle for a High-Efficiency Power Audio Amplifier for Use with a Digital Preamplifier	Jørgen Arendt Jensen	984	
<i>Digital audio directly regulates the power supply for a class-B amplifier in anticipation of the amplifier's analog audio input.</i>			
ENGINEERING REPORTS			
A New Principle for an All-Digital Preamplifier and Equalizer	Jørgen Arendt Jensen	994	
<i>Gain and equalization are adjusted by a preamplifier operating on the digital signal for a Compact Disc.</i>			
COMMUNICATIONS			
Wigner Distribution Analysis of Filters with Perceptible Phase Distortion	D. Preis, F. Hlawatsch, P. J. Bloom, and J. A. Deer	1004	
<i>The time-frequency behavior of anti-aliasing filters is computed using the Wigner distribution. Analytical results are keyed to audible differences.</i>			
LETTERS TO THE EDITOR			
Comments on "Spaciousness and Localization in Listening Rooms and Their Effects on the Recording Technique"	Stanley P. Lipshitz	1013	
Author's Reply	David Griesinger	1013	
Reply to Comments	Michael Gerzon	1013	
STANDARDS			
Standards News from JASA (Reprint, JASA, Vol. 82(5), pp. 1848-1852, 1987 November)		1015	
TECHNICAL COMMITTEE REPORTS			
Minutes of the Meeting of the AES Digital Audio Technical Committee (1987 March 10)	Bart N. Locanthi	1020	
FEATURES			
83rd Convention Report		1028	
Exhibitors		1044	
Program		1048	
New AES Officers 1987-1988		1067	
1988 AES International Sections Directory		1072	
DEPARTMENTS			
Upcoming Meetings	1080	Available Literature	1085
News of the Sections	1080	Membership Information	1087
Sound Track	1082	Call for Papers— 3rd Regional Convention, Melbourne, 1988	1090
Abstracts of Interest	1083	Index to Volume 35	1092
New Products and Developments	1084	AES Conventions and Conferences	1098

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 36 NUMBER 1/2

1988 JANUARY/FEBRUARY

CONTENTS

PAPERS

- A Technique for Displaying the Current and Voltage Output Capability of Amplifiers and Relating This to the Demands of Loudspeakers** Peter J. Baxandall 3
A test method reveals a power amplifier's sometimes idiosyncratic current-overload behavior, important when operating with a complex load. Test results are compared with those obtained using music signals and a loudspeaker.

ENGINEERING REPORTS

- Noise-Dependent Sound Reproduction in a Car: Application of a Digital Audio Signal Processor** ... W. J. W. Kitzen, J. W. Kemna, W. F. Druyvesteyn, C. L. C. M. Knibbeler, and A. T. A. M. van de Voort 18
Road noise and mechanical noise spoil the reproduction of speech and music in an automobile. Automatic compression and control of signal volume can counteract such interference unobtrusively.
- Graceful Degradation of Digital Audio Transmission Systems** K. A. Schouhamer Immink 27
Conventional digital systems fail catastrophically if the transmission bandwidth is reduced below a design threshold. A new coding method accommodates bandwidth reduction (or expansion) with corresponding adjustment in signal resolution.

COMMUNICATIONS

- Forensic Audio and Video—Theory and Applications** Tom Owen 34
Audio and video tapes entered as legal evidence are often examined for authenticity or processed to clarify their content. Analysis may identify a tape's machine-origin and disclose whether or not it has been altered.

FEATURES

- 6th AES International Conference: Sound Reinforcement** 45
- 84th AES Convention Preview** 50
- Exhibit Previews** 54
- Exhibitors** 93

DEPARTMENTS

- | | | | |
|---|----|---|-----|
| Review of Acoustical Patents | 42 | Call for Papers—3rd Regional Convention, Melbourne, 1988 | 105 |
| News of the Sections | 95 | Call for Papers—85th Convention, Los Angeles, 1988 | 107 |
| Upcoming Meetings | 96 | Information for Authors of Convention Papers | 109 |
| Sound Track | 96 | | |
| Available Literature | 98 | | |
| Membership Information | 99 | | |
| | | AES Special Publications | 110 |
| | | AES Conventions and Conferences | 112 |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 36 NUMBER 3

1988 MARCH

CONTENTS

PAPERS

- Simulation of Loudspeaker Crossover Filters with a Digital Signal Processor** R. M. Aarts and A. J. M. Kaizer 115
The winner among competing crossover filters having nearly the same frequency response can be judged only by listening. Aural comparisons are fast and accurate when the analog filters are simulated by a digital processor.

- The Modification of Timbre by Resonances: Perception and Measurement** Floyd E. Toole and Sean E. Olive 122
Perceived resonant coloration, produced either by the electronic hardware or the acoustic environment, depends upon program material, hearing acuity, the resonance frequency, Q, and amplitude, and upon influences such as reverberation and delay.

- A Bayesian Analysis of A-B Listening Tests** Mark Srednicki 143
Seemingly chance results do not rule out an audible difference between A and B if the test is shorter than several hundred trials.

ENGINEERING REPORTS

- Reduction of Peak/rms Ratio of Speech by Amplitude Compression and Quadratic Phase Dispersion** John T. Lynch 147
Intentional phase dispersion of the speech signal permits amplitude compression greater than is ordinarily achieved. Preliminary results may be useful in AM (especially shortwave) broadcasting.

STANDARDS

- Minutes of the Meeting of the AES Digital Audio Standards Committee (1987 October 16)** Bart N. Locanthi 153

FEATURES

- AES 6th International Conference: Sound Reinforcement—Preliminary Program** 164
1888–1988: A Hundred Years of Magnetic Sound Recording Friedrich Karl Engel 170

DEPARTMENTS

- | | | | |
|-------------------------------|-----|--|-----|
| Review of Acoustical Patents | 159 | Available Literature | 191 |
| News of the Sections | 180 | Membership Information | 194 |
| Sound Track | 185 | Call for Papers—AES 85th Convention, Los Angeles, 1988 | 196 |
| Upcoming Meetings | 188 | AES Special Publications | 198 |
| New Products and Developments | 189 | AES Conventions and Conferences | 200 |

CONTENTS

PAPERS

Wigner Representation of Loudspeaker Responses in a Living Room
..... D. J. Verschuur, A. J. M. Kaizer, W. F. Druyvesteyn, and D. de Vries 203
Several related distributions are compared with the Wigner distribution as evaluations of loudspeaker response in a reflective room.

Reduction of Transistor Slope Impedance Dependent Distortion in Large-Signal Amplifiers
..... Malcolm Hawksford 213
Frequency-dependent nonlinear distortion, not easily reduced by negative feedback, is generated by signal-modulated transistor impedances. Circuits are developed to minimize their influence.

Environmental Effects on the Speed of Sound Dennis A. Bohn 223
Variations in temperature and humidity may change room equalization abruptly, affecting both relative frequency response and high-frequency sound pressure levels.

COMMUNICATIONS

Increasing the Life of Your Audio Tape Jim Wheeler 232
The longevity of tape records depends on magnetic formulation, storage temperature and humidity, and exercise. Here is advice on preserving recorded signals.

STANDARDS

Standards News from JASA (Reprint JASA, Vol. 83(1), pp. 389-395, 1988 January) 237

FEATURES

The Compact Disc Formats: Technology and Applications Ken C. Pohlmann 250

DEPARTMENTS

Review of Acoustical Patents	244	Membership Information	298
News of the Sections	288	Audio Engineering Society Bylaws	304
Upcoming Meetings	290	Call for Papers—AES 85th Convention, Los Angeles, 1988	308
Sound Track	290	AES Special Publications	310
New Products and Developments	292	AES Conventions and Conferences	312
Available Literature	295		

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 36 NUMBER 5

1988 MAY

CONTENTS

PAPERS

- The Analytic Impulse** Andrew Duncan 315
Mathematical analysis of real data may yield unreal results (events that precede causes, for instance), and the properties of much otherwise useful mathematics make such disappointments inevitable. If the data are judiciously windowed, the results can be interpreted more easily. Impulse responses of a loudspeaker are shown as examples.
- A New Windowing Technique for Digital Harmonic-Distortion Measurement** Robert W. Adams 328
Measuring an 18-bit A/D converter for harmonic distortion below -100 dB becomes possible using a digital-windowing procedure. Choice of input frequency is unconstrained. Results are confirmed for harmonics greater than -90 dB by comparison with an analog method.
- Cluster Suitability Predictions Simplified** Bob Thurmond 337
A single loudspeaker cluster may or may not provide acceptable speech intelligibility in a room, but acceptability is predictable. Room volume, reverberation time, loudspeaker directivity, and maximum listener distance are the governing quantities. Suggested first choice for a fix of poor results is increased room absorption.
- The Use of TV Holography (ESPI) for Loudspeaker Chassis and Cabinet Modal Analysis**
 John R. Tyrer 342
Micrometer displacements of transducers or their enclosures are observed and measured using laser speckle interferometry, which exploits the interference between object illumination and a reference wave. This optical combination is linked with a video camera. Procedures are described for both continuous and pulsed laser sources.

ENGINEERING REPORTS

- Sampling-Frequency Synchronization with Minimal Delay** N. H. C. Gilchrist 350
Digital signals from independent sources must be synchronized before they can be digitally mixed. Temporary storage allows all samples to be accessed by a single clock, but some samples may have to be repeated, discarded, or appreciably delayed in the process. The audibility of these sacrifices is appraised.

STANDARDS

- Standards News from JASA (Reprint JASA, Vol. 83(3), pp. 1203-1205, 1988 March)..... 359

FEATURES

- 84th Convention Report 362
 Exhibitors 375
 Program 378
- Magnetic Sound Recording in Europe Up to 1945 Heinz H. K. Thiele 396

DEPARTMENTS

- | | |
|---|---|
| News of the Sections 409 | Membership Information 421 |
| Sound Track 413 | In Memoriam 433 |
| Upcoming Meetings 414 | Membership Application Form 435 |
| New Products and Developments 416 | AES Special Publications 438 |
| Available Literature 418 | AES Conventions and Conferences 440 |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 36 NUMBER 6

1988 JUNE

CONTENTS

PAPERS

Subwoofer Performance for Accurate Reproduction of Music

Louis D. Fielder and Eric M. Benjamin 443

Records with audible content below 30 Hz are rare, but some Compact Discs require a response beginning at 10 to 12 Hz for faithful reproduction at 110- to 120-dB sound pressure level. A suitable subwoofer, with low cutoff in the 10-Hz range, must be reasonably free of harmonic distortion and noise, particularly above 2 kHz. Room gain partly eases loudspeaker requirements, though the room itself may respond with rattles and buzz. Currently available subwoofers in a test sample were not satisfactory.

Linearly Swept Frequency Measurements, Time-Delay Spectrometry, and the Wigner Distribution

Mark A. Poletti 457

Measurements using linear sweep frequency inputs are defined in terms of the Wigner distribution. The usual time-delay spectrometry procedure is incomplete; an additional operation yields an improved transfer-function estimate while ignoring the limitation on sweep rate. Energy-time and energy-time-frequency measurements are reexamined.

ENGINEERING REPORTS

An 18-Bit Digital-to-Analog Converter for High-Performance Digital Audio Applications

Joel M. Halbert and Mark A. Shill 469

Signal processing with more than 16 bits is needed to realize the full potential of a 16-bit product. Design of this 18-bit converter is based on careful choices of binary weighting, thermal design, and noise-source evasion.

A Dynamic Phase Meter for Program Material

John Monforte 481

An aid to the broadcast engineer is this program meter's indication of stereo signal coherence. Stereo X and Y signals are first matrixed to their M-S counterparts, and the resulting vu-meter deflection is proportional to the ratio $|S/M|$.

Measuring Equipment for the Estimation of "Pop" Sensitivity of Microphones

W. Wienhöfer and J. Sennheiser 487

An acoustic pop generator produces reproducible transients for testing microphone susceptibility to this type of noise. Experimental results are shown for a microphone with and without its protective basket.

FEATURES

Digital Audio Recorders

John Watkinson 492

DEPARTMENTS

News of the Sections	510	Abstracts of Interest	521
Upcoming Meetings	516	Membership Information	522
Sound Track	516	In Memoriam	529
New Products and Developments	517	Membership Application Form	531
Available Literature	520	AES Special Publications	534
AES Conventions and Conferences		536	

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 36 NUMBER 7/8

1988 JULY/AUGUST

CONTENTS

PAPERS

Calculation of the Sound Radiation of a Nonrigid Loudspeaker Diaphragm Using the Finite-Element Method Arie J. M. Kaizer and Ad Leeuwestein 539
The finite-element method is applied to calculating the motion of a loudspeaker diaphragm and its resulting sound radiation. Examples use an ideal, rigid cone and a real, 4-inch diameter loudspeaker.

Loudspeaker Power Amplifiers with Load-Adaptive Source Impedance David Birt 552
Additional amplifier components maintain the amplifier-loudspeaker low-frequency loop resistance constant, thereby canceling changes in sensitivity and frequency response provoked by voice-coil temperature rise.

ENGINEERING REPORTS

The Design of a Digital Signal Peak Limiter for Audio Signal Processing Dan Mapes-Riordan and W. Marshall Leach, Jr. 562
Digital processing permits adjustment of signal gain in advance of an otherwise excessive signal amplitude. Gain changes occur only at signal zero-crossings and are therefore usually inaudible and relatively distortionless.

Improvement in Dome Loudspeaker Characteristics by Using a Spherical-Wave-Front Horn Baffle Junichi Hayakawa, Shiro Iwakura, Kaoru Yamazaki, and Susumu Matsuoka 575
A baffle shaped to accommodate a spherical wave front improves efficiency and reduces reflective and diffractive interference. Experimental results are shown using a 26-mm dome driver.

LETTERS TO THE EDITOR

Comments on "Choosing the Right Microphone by Understanding Design Tradeoffs" James B. Lee 585
Author's Reply Bruce Bartlett 585

STANDARDS

Standards News from JASA (Reprint JASA, Vol. 83(5), pp. 1984-1985, 1988 May) 586

FEATURES

AES 6th International Conference Report 588
Program 598
Magnetic Tape—From the Early Days to the Present Friedrich Karl Engel 606
AES 85th Convention, Los Angeles, Announcement 626

DEPARTMENTS

News of the Sections	617	AES Annual Report	634
Sound Track	621	Call for Papers—86th Convention,	
Upcoming Meetings	622	Hamburg, 1989	635
New Products and Developments	623	Information for Authors of Convention	
Available Literature	625	Papers	637
Membership Information	628	AES Special Publications	638
In Memoriam	633	AES Conventions and Conferences	640

CONTENTS

PAPERS

- Proposed Technique for Earphone Calibration** ... J. S. Russotti, T. P. Santoro, and G. B. Haskell 643
Earphone response is measured using a modified Zwislocki coupler mounted in a dummy head. With proper correction, the results can be compared with the head's equivalent field response. The method is useful for nearly all types of headphones.
- Simulation and Optimization of Multiway Loudspeaker Systems Using a Personal Computer** Witold Waldman 651
A computer program simulates the acoustic sum of driver outputs in a two-way or three-way system. The optimization process is flexible, allowing substitution of drivers, crossover frequencies, and driver positions.
- The Subjective Effect and Measurement of ADC-DAC Transfer Characteristic Discontinuity** N. H. C. Gilchrist 664
Experiments with a 14-bit converter disclose (depending on program material) the detectability of a single quantum discontinuity located at the center of the transfer characteristic. Larger discontinuities, farther removed from the center, may escape notice.
- A Method of Generating and Controlling Musical Asymmetrical Spectra** J.-P. Palamin, P. Palamin, and A. Ronveaux 671
Synthesized tones with adjustable formants are generated by systematically altering the individual component amplitudes in a frequency-modulated signal.

ENGINEERING REPORTS

- Results of the 1986 AES Audiometric Survey** Charles Martinez and Samuel Gilman 686
Tests of AES members show a small hearing deficiency added to the normal loss attributed to aging. Wide individual variations in hearing threshold are found in the range from 3 to 6 kHz.

STANDARDS

- Standards News from JASA (Reprint JASA, Vol. 84(1), pp. 453-456, 1988 July)** 693
AES Standards News: New Working Groups Approved 696

FEATURES

- AES 2nd Regional Convention Preprint List** 692
AES 85th Convention Preview 698
Exhibit Previews 702
Exhibitors 735

MESSAGE TO MEMBERS

- AES Educational Foundation Selects Recipients** 747

DEPARTMENTS

- | | | | |
|-----------------------------------|-----|--|-----|
| News of the Sections | 737 | Membership Information | 748 |
| Upcoming Meetings | 740 | Membership Application Form | 755 |
| Sound Track | 741 | AES Special Publications | 758 |
| Available Literature | 744 | AES Conventions and Conferences | 760 |

CONTENTS

PAPERS

- Acoustic Load and Transfer Functions in Rooms at Low Frequencies** Tomas Salava 763
At low frequency, room dimensions and loudspeaker position peculiarly modify the loudspeaker's response. Acoustic load and transfer impedances are useful measures of overall performance, especially in small rooms.
- Compact Ribbon Tweeter/Midrange Loudspeaker** J. A. M. Nieuwendijk 776
Response embracing midrange to ultrasonic frequencies is achieved by combining a ribbon membrane with an air-volume spring. Sensitivity of a model loudspeaker is 94 dB SPL at one meter and one watt.

ENGINEERING REPORTS

- A Loudspeaker Motor Structure for Very High Power Handling and High Linear Excursion** Douglas J. Button 788
An optimized design for a woofer motor reduces nonlinear excursion and thermal power compression at levels greater than 100 watts. Choosing an aluminum voice coil instead of copper provides a significant advantage.
- Audio for the Elderly** Edward W. Herold 798
With increasing age, hearing deteriorates, markedly above 500 Hz. To benefit older listeners, consumer and sound reinforcement electronics might well include capabilities for high-frequency boost and amplitude compression.

FEATURES

- On Improvements of Magnetic Tape Shown by Measurements on Early and Newer Tapes** Rudolph Müller 802
- Review of Society's Sustaining Members** 822

DEPARTMENTS

- | | | | |
|--|-----|--|-----|
| News of the Sections | 837 | Available Literature | 841 |
| Upcoming Meetings | 838 | Membership Information | 843 |
| Sound Track | 839 | AES Special Publications | 846 |
| New Products and Developments | 840 | AES Conventions and Conferences | 848 |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 36 NUMBER 11

1988 NOVEMBER

CONTENTS

PAPERS

The Implementation of Recursive Digital Filters for High-Fidelity Audio Jon Dattorro 851
While the theoretical design of a digital filter may be routine, the hardware choices for its realization contain certain pitfalls. The author shows where the pitfalls are and how to avoid them.

Approximation Formulas for Error Risk and Sample Size in ABX Testing Herman Burstein 879
Blind testing of listener perception involves calculable risks of coming to the wrong conclusion. Leventhal's tabular results are extended with formulas for general values of sample size and response probability.

ENGINEERING REPORTS

Enhancement of Forensic Audio Recordings Bruce E. Koenig 884
Recordings useful as legal evidence are often made in miserable circumstances. Using laboratory techniques, the FBI improves the intelligibility of such recordings for presentation in a court of law. Selection and responsibilities of FBI personnel are outlined.

Effect of DAC Deglitching on Frequency Response Robert Bristow-Johnson 895
Switching noise in the digital-to-analog converter must be suppressed for high-quality audio, but the usual means for suppression degrades frequency response. The response defect can be compensated in the program material.

FEATURES

AES 3rd Regional Convention Report 906
Exhibitors 912
Program 914
Boston Symphony Hall: An Acoustician's Tour Leo L. Beranek 918

DEPARTMENTS

Review of Acoustical Patents	904	New Products and Developments	935
News of the Sections	932	Available Literature	937
Upcoming Meetings	932	Membership Information	939
Sound Track	934	AES Special Publications	942
AES Conventions and Conferences		944	

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 36 NUMBER 12

1988 DECEMBER

CONTENTS

President's Message Stanley P. Lipshitz 947

PAPERS

General Equivalent Electric Circuits for Acoustic Horns J. Kergomard 948
Equivalent circuits, composed of lumped elements, represent the acoustic input impedances and transfer functions of tubes and horns. Results are applied to design of a saxophone mouthpiece.

Improvements in FMX Technology Emil L. Torick and Aldo G. Cugnini 956
Design parameters are detailed for this FM broadcast system. An additional companded stereo-difference signal yields perceived noise levels that are close to those of conventional monophonic reception. Effective service area is increased.

ENGINEERING REPORTS

High Frequency Phase Response Specifications—Useful or Misleading? Deane Jensen 968
Constant group delay (or linear phase) is crucial for waveform fidelity in electronic components, and the deviations from linear phase or constant delay (as functions of frequency) are clear assessments of quality. Phase measurements at only one or two frequencies convey no useful information.

A Holographic Approach to Acoustic Control A. J. Berkhout 977
In principle, an electroacoustically reconstructed sound field can be indistinguishable from the original. A practical system, based on holographic reconstruction, generates a field with as small an error as desired. The author finds it the ultimate method for sound reproduction or reinforcement.

STANDARDS

Standards News from JASA (Reprint, JASA, Vol. 84(3), pp. 1123–1125, 1988 September) 996

FEATURES

85th Convention Report 1002

Exhibitors 1018

Program 1021

New AES Officers 1988–1989 1036

1989 AES International Sections Directory 1039

DEPARTMENTS

Review of Acoustical Patents 999 **Membership Information** 1060

News of the Sections 1048 **In Memoriam** 1061

Upcoming Meetings 1050 **Call for Papers—AES 4th Regional**

Sound Track 1051 **Convention, Tokyo, 1989** 1062

Abstracts of Interest 1053 **Index to Volume 36** 1064

New Products and Developments 1054 **AES Special Publications** 1070

Available Literature 1057 **AES Conventions and Conferences** 1072

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 37 NUMBER 3

1989 MARCH

CONTENTS

PAPERS

Sound Radiation from Circular Stretched Membranes in Free Space J. H. Stregg 107
A stretched membrane obviously differs from a rigid piston, and the two can be expected to behave very differently as sound radiators. The circular membrane is analyzed with an exact mathematical model. Results are compared with the experimental response of an electrostatic loudspeaker.

A Model of Loudspeaker Driver Impedance Incorporating Eddy Currents in the Pole Structure John Vanderkooy 119
A loudspeaker voice coil (with its magnetic iron) is not the equivalent of a simple lossy inductor. Impedance measurements and eddy-current theory reveal an equivalent "semi-inductor," with novel consequences for loudspeaker-motor efficiency and heat dissipation.

Distortion Reduction in Moving-Coil Loudspeaker Systems Using Current-Drive Technology P. G. L. Mills and M. O. J. Hawksford 129
Several sources of nonlinear distortion, active when the loudspeaker is driven by a voltage generator, disappear if the driver is a current generator instead. The usually unsatisfactory frequency response resulting from current drive can be corrected with low-level equalization or with motional feedback.

ENGINEERING REPORTS

Analysis and Detection of Acoustically Coupled DTMF Signals James H. Hahn 149
Acoustic dual-tone signals, fed to the telephone network, may be received incorrectly by currently installed digital frequency detectors. For each tone, an optimum number of measured zero crossings would minimize errors, making possible receivers of greater reliability.

CORRECTIONS

Correction to "The Analytic Impulse" 156
Correction to "Improvements in FMX Technology" 156

STANDARDS

Standards News from JASA (Reprint, JASA, Vol. 85(1), pp. 517-519, 1989 January) 158

FEATURES

AES 7th International Conference: Audio in Digital Times—Preliminary Program 164
Updates and Additions to the AES 1989 International Sections Directory 175

DEPARTMENTS

Review of Acoustical Patents	161	In Memoriam	191
News of the Sections	170	Call for Papers—AES 87th Convention, New York, 1989	192
Sound Track	176	Information for Authors of Convention Papers	194
Upcoming Meetings	178	Membership Application Form	195
New Products and Developments	179	AES Special Publications	198
Available Literature	182		
Membership Information	184		
		AES Conventions and Conferences	200

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 37 NUMBER 4

1989 APRIL

CONTENTS

PAPERS

- Time Dependence of Loudspeaker Power Output in Small Rooms** Glyn Adams 203
A loudspeaker's output power is modified by the geometry of the space into which it radiates. In a small room, all of the room boundaries contribute to this modification, largely so at frequencies where the room is resonant. Room-loading varies with time during transient signals.
- Subjective Evaluation of Angular Displacement between Picture and Sound Directions for HDTV Sound Systems** Setsu Komiyama 210
Conventional two-channel stereo fails to pinpoint a satisfactory coincidence of sound and picture images for high-definition television. Three, four, or five channels have been proposed as necessary, but there is not agreement on their number or disposition. A subjective experiment evaluates viewer annoyance versus angular displacement of visual and sound sources, suggesting an additional center channel as sufficient for horizontal localization.

ENGINEERING REPORTS

- New Magnetic System Designs for Sound-Reinforcement Loudspeaker Applications** Raymond J. Newman and Paul F. Fidlin 215
Loudspeaker motors using new magnetic materials can be smaller and lighter than their predecessors. A redesigned compression driver is more compact than its original and weighs one-third as much. Possibilities are examined for weight reduction in sound-reinforcement arrays.
- A Feedforward Side-Chain Limiter/Compressor/De-esser with Improved Flexibility** A. J. Oliveira 226
The controls of this dynamic limiter provide independent adjustment of compression, threshold, and soft or hard limiting, with constant before-threshold gain. Use of a feedforward side chain results in attack and release times that are independent of compression-ratio settings.

EDUCATION NEWS

- Audio Engineering Society Educational Foundation Awards Program** 241
- Richard Heyser Scholarship Loan Fund Is Tax Exempt** 241

FEATURES

- AES 4th Regional Convention: Sound Engineering Today and Tomorrow** 242
- The Spectral Amplitude Distribution of Selected Compact Discs** R. A. Greiner and Jeff Eggers 246

DEPARTMENTS

- | | | | |
|--|-----|--|-----|
| News of the Sections | 276 | Membership Information | 289 |
| Upcoming Meetings | 280 | AES Bylaws | 296 |
| Sound Track | 280 | Call for Papers—AES 87th Convention, | |
| New Products and Developments | 284 | New York, 1989 | 300 |
| Available Literature | 287 | AES Special Publications | 302 |
| | | AES Conventions and Conferences | 304 |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 37 NUMBER 5

1989 MAY

CONTENTS

Editor's Message: Staff Changes in the Publications Office Robert O. Fehr 307

PAPERS

An Introduction to Band-Pass Loudspeaker Systems Earl R. Geddes 308
A driver working into enclosures fore and aft, with ports in one or both, generates a band-pass response. Crossover responsibilities can then be partly transferred from networks to reproducers, with reduced cost, improved cutoff slopes, and greater passband efficiency.

Impulse Measurement of Acoustic Impedance Josef Merhaut 343
A pulsed acoustic input is the foundation for measuring the input and transfer impedances of tubes and horns. The method is fast and uses conveniently available equipment.

Computation of Diffraction for Loudspeaker Enclosures Juha Backman 353
The general theory of diffraction guides a computation of the pressure, energy, and polar responses of a loudspeaker. Taken into account are the diffractions provoked by its enclosures, assuming that the enclosure is convex and formed (as it usually is) of surfaces that are plane and nonabsorbing.

Transformed Binomial Confidence Limits for Listening Tests Herman Burstein 363
Confidence limits are derived for the percentage of correct listening-test responses that are known (heard), differing from those responses that are merely correct guesses. Results apply to both ABX and multiple-choice testing.

STANDARDS

Standards News from JASA (Reprint JASA, Vol. 85(3), pp. 1384-1385, 1989 March) 368

FEATURES

86th Convention Report 370
 Exhibitors 384
 Program 387

DEPARTMENTS

News of the Sections 401	Membership Information 408
Sound Track 403	Call for Papers—AES 87th Convention, New York, 1989 412
Upcoming Meetings 404	AES Special Publications 414
New Products and Developments 405	AES Conventions and Conferences 416
Available Literature 407	

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 37 NUMBER 6

1989 JUNE

CONTENTS

PAPERS

- Transfer-Function Measurement with Maximum-Length Sequences**
 Douglas D. Rife and John Vanderkooy 419
Direct measures of a system's impulse response forces compromise with either system overload or noise contamination. The same response is acquired more easily using a particular repetitive binary-signal input. The method is alternative to time-delay spectrometry or to fast-Fourier-transform measurements.
- A New Method for the Design of Crossover Filters** R. M. Aarts 445
An adjustable digital filter feeds each driver of an experimental loudspeaker. Optimal choice of filter coefficients enables the loudspeaker to mimic a given response, real or imagined. Impersonations of several commercial loudspeakers are judged using both listening tests and comparative measurements.
- Application of Digital Filters to Loudspeaker Crossover Networks**
 Rhonda Wilson, Glyn Adams, and Jonathan Scott 455
We approach audio systems that "perform all necessary signal processing in the digital domain" before converting to analog signals for the loudspeakers. Crossover functions and driver equalization might as well be included, and the methodology for doing so is explored. Listeners test the audibility of two off-axis crossover notches.

ENGINEERING REPORTS

- Topological Enhancements of Translinear Two-Quadrant Gain Cells**
 Malcolm O. J. Hawksford and P. G. L. Mills 465
The authors review the shortcomings of bipolar voltage-controlled amplifiers—in particular, their increased distortion at high signal attenuation—and suggest circuits that offer improvement. Experimental noise and distortion measurements are included.
- A Stereo 16-Bit Delta-Sigma A/D Converter for Digital Audio**
 D. R. Welland, B. P. Del Signore, E. J. Swanson, T. Tanaka, K. Hamashita,
 S. Hara, and K. Takasuka 476
Theory of the delta-sigma modulator is reviewed and applied to design of a two-channel, oversampled, A/D converter with a sampling rate of 3 MHz. Measured noise spectra and S/N ratios are shown.

LETTERS TO THE EDITOR

- Comments on "The Implementation of Recursive Digital Filters of High-Fidelity Audio"**
 Louis R. Eagle 486
- Author's Reply** Jon Dattorro 486

STANDARDS

- Standard News from JASA (Reprint JASA, Vol. 85(5), pp. 2239-2240, 1989 May)** 487

FEATURES

- Jack Mullin: The Man and His Machines** Peter Hammar 490

DEPARTMENTS

- | | | | |
|--|-----|---------------------------------------|-----|
| News of the Sections | 514 | Available Literature | 528 |
| Sound Track | 520 | Membership Information | 529 |
| Upcoming Meetings | 524 | In Memoriam | 531 |
| New Products and Developments | 526 | AES Special Publications | 534 |
| AES Conventions and Conferences | | 536 | |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 37 NUMBER 7/8

1989 JULY/AUGUST

CONTENTS

PAPERS

- The Detection of Reflections in Typical Rooms** Sean E. Olive and Floyd E. Toole 539
Reflective environments obviously modify the quality of reproduced sound. For small rooms and stereophonic reproduction, past research does not completely define whether various reflections are welcome or unwelcome. Experimental results extend those evaluations.
- Acoustic Waveguide Theory** Earl R. Geddes 554
Horn theory is inexact. A few horn geometries permit an exact wave description in terms of a single variable. One such geometry yields an apparently ideal constant-directivity horn.
- An Introduction to Electromagnetic Compatibility (EMC) and Electromagnetic Interference (EMI) for Audio System Designers** Philip Giddings 570
Electromagnetic noise and interference are avoided by well-known techniques. The author reviews recommended practice in equipment interconnection, shielding, cabling, and grounds.
- Electroacoustic-Analogous Circuit Models for Filled Enclosures** W. Marshall Leach, Jr. 586
A loudspeaker enclosure's acoustic impedance is altered by adding filling material. Circuit analogs are developed to represent the modified box compliance and the thermodynamic and kinetic behavior of the filler.

ENGINEERING REPORTS

- A Digital Approach to Time-Delay Spectrometry** Richard Greiner, Jamsheed Wania, and Gerardo Noejovich 593
TDS measurements are usually made with analog equipment. Here the same measurement is accomplished digitally, using an IBM-AT computer and appropriate hardware, and produces energy-time results as well.

FEATURES

- An Afternoon with: John K. Hilliard** 605
- AES 7th International Conference Report** 608
- Program** 614

DEPARTMENTS

- | | | | |
|--|-----|---------------------------------------|-----|
| Review of Acoustical Patents | 603 | Available Literature | 645 |
| News of the Sections | 630 | Membership Information | 648 |
| Upcoming Meetings | 632 | In Memoriam | 652 |
| Sound Track | 633 | AES Annual Report | 653 |
| New Products and Developments | 640 | AES Special Publications | 654 |
| AES Conventions and Conferences | | 656 | |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 37 NUMBER 9

1989 SEPTEMBER

CONTENTS

PAPERS

- Sound Intensity and Interaural Cross-Correlation Measurements Using Time-Delay Spectrometry** John Konnert, Farrel Becker, and Charles Bilello 659
Spatially orthogonal components of the early reflections in a control room are measured using time-delay spectrometry. Interaural data yield interaural cross-correlation results for the same environment.
- Complex Time-Response Using Time-Delay Spectrometry** Peter D'Antonio and John Konnert 674
Time-delay spectrometry measures the complex time response of a digital delay device, a flat panel, and a reflection phase grating. The measurement theory is reviewed and extended.
- Acoustic Alignment of Loudspeaker Drivers by a Nonsymmetrical Crossovers of Different Orders** B. Hillerich 691
Separation of driver acoustic centers is compensated by choosing low-frequency and high-frequency crossover filters of different order and, therefore, different group delay. An example is shown.
- Determination of Loudspeaker Driver Parameters Using a System Identification Technique** M. H. Knudsen, J. Grue Jensen, V. Julskjaer, and P. Rubak 700
A simultaneous measurement of driver voltage, current, and displacement provides accurate estimates of the driver parameters. The method is confirmed by experiment.
- The Differential Time-Delay Distortion and Differential Phase-Shift Distortion as Measures of Phase Linearity** W. Marshall Leach, Jr. 709
Acoustic signals can be viewed as modulated carriers. Bandlimited systems delay carrier and modulation envelope unequally. The temporal delay difference is developed as a phase distortion measure.

FEATURES

- An Afternoon with: Bill Putnam** 723
- AES 87th Convention Preview** 733
- Exhibit Previews** 736

DEPARTMENTS

- | | | | |
|--|-----|--|-----|
| Review of Acoustical Patents | 716 | Membership Information | 783 |
| News | 719 | Call for Papers—AES 88th Convention, Montreal, 1990 | 784 |
| Upcoming Meetings | 765 | Information for Authors of Convention Papers | 786 |
| News of the Sections | 766 | Membership Application Form | 787 |
| Sound Track | 770 | AES Special Publications | 790 |
| New Products and Developments | 778 | | |
| Available Literature | 780 | AES Conventions and Conferences | 792 |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 37 NUMBER 10

1989 OCTOBER

CONTENTS

PAPERS

Self-Similarity and Fractals in Science and Art Manfred R. Schroeder 795
Sooner or later, the strangest of purely mathematical inventions are retrieved to illuminate our experimental perceptions. Recent advances—and their limits—in describing chaotic nonlinear systems are reviewed, and a self-similar musical example challenges our presuppositions concerning pitch.

Transconductance Power Amplifier Systems for Current-Driven Loudspeakers
 P. G. L. Mills and M. O. J. Hawksford 809
Advantages accrue in choosing to drive a loudspeaker with current that is independent of loudspeaker impedance (the dual of an independent driving voltage). The wisdom of this choice is confirmed in experiments with an amplifier especially designed for current drive.

ENGINEERING REPORTS

XY and MS Microphone Techniques in Comparison Manfred Hibbing 823
With ideal microphones, XY and MS arrangements are equivalent; each is transformable to the other. In practice, microphone imperfections get in the way. Faults accounted for, MS is more reliable and less prone to error.

Stereo Sound Recording with Shotgun Microphones Henning Gerlach 832
Under some circumstances in television or motion-picture production, interference-tube microphones can prove useful as a stereo pair. Experimental responses are given for XY and MS configurations, and choices are suggested for microphone design and placement.

LETTERS TO THE EDITOR

Comments on "Diffusing Surfaces in Concert Halls: Boon or Bane?"
 John Konnert and Peter D'Antonio 839

Author's Reply Jeffrey Borish 843

A Hilliard Reminiscence Leslie E. Gilliss 845

CORRECTIONS

Corrections to "Topological Enhancements of Translinear Two-Quadrant Gain Cells" 845

FEATURES

4th Regional Convention Report 846

Review of Society's Sustaining Members 851

DEPARTMENTS

News	848	Available Literature	888
News of the Sections	876	Membership Information	891
Upcoming Meetings	878	In Memoriam	892
Sound Track	879	AES Special Publications	894
New Products and Developments	884	AES Conventions and Conferences	896

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 37 NUMBER 11

1989 NOVEMBER

CONTENTS

PAPERS

- Multiple-Point Equalization in a Room Using Adaptive Digital Filters** S. J. Elliott and P. A. Nelson 899
Equalizing the acoustic response at one point of an environment may degrade the response at other points. A better procedure equalizes at several points together, using a mean-squares criterion to specify the equalizer. A modeled automobile interior furnishes an example.
- Loudspeaker Cabinet Edge Diffraction** James Porter and Earl Geddes 908
Analyses using the geometric theory of diffraction and the finite element method yield similar results. With axisymmetric radiators as examples, the useful wavelength ranges and advantages of the two methods are compared.

ENGINEERING REPORTS

- Adaptive Loudspeaker System** Joji Kuriyama and Yasuyuki Furukawa 919
An adaptive filter corrects the amplitude and phase responses of a loudspeaker. Experiments achieve the desired correction in seconds, using either music or white noise as the input signal.
- Broadcast-Quality Speech from Diving Helmets** D. J. Meares 927
Acquiring speech of broadcast quality from a diver presents unusual problems. Diver safety and comfort, avoiding valve and breathing noises, and determining appropriate equalizations are matters reported here.

COMMUNICATIONS

- An Improved Preemphasis Standard for AM Broadcasting** A. N. Thiele 934
Thoughtless receiver design and aggressive transmission practice have damaged the quality of AM reception. The author proposes a preemphasis-deemphasis characteristic, and the networks for its realization, to improve the received signal while minimizing adjacent-channel interference. Also discussed are optimal means for eliminating the adjacent-carrier heterodyne.

STANDARDS

- AES Request to CCIR** Robert A. Finger 940
- Standard News from JASA (Reprint JASA, Vol. 86(3), pp. 1195-1199, 1989 September)** 942

FEATURES

- Tube Manufacturing at Western Electric: The WE 300B** Attila R. Balaton 949

DEPARTMENTS

- | | | | |
|--|-----|--|-----|
| Review of Acoustical Patents | 947 | Sound Track | 964 |
| News | 948 | New Products and Developments | 967 |
| News of the Sections | 960 | Available Literature | 972 |
| Upcoming Meetings | 962 | AES Special Publications | 974 |
| AES Conventions and Conferences | | 976 | |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 37 NUMBER 12

1989 DECEMBER

CONTENTS

President's Message Benjamin Bernfeld 979

PAPERS

Chaos, Oversampling, and Noise Shaping in Digital-to-Analog Conversion M. O. J. Hawksford 980

"Information theory predicts that when a bandlimited signal is oversampled, the output data can tolerate a reduction in amplitude resolution yet maintain a similar in-band signal-to-noise ratio." The author demonstrates how this principle might be realized using high (x 200) oversampling and noise shaping, with reduced stress on performance of the digital-to-analog converter.

Application of Speech Intelligibility to Sound Reinforcement Don Davis and Carolyn Davis 1002
Several methods have been developed to measure speech intelligibility instrumentally as opposed to using word lists and a panel of listeners. This paper defines what is measured, compares the results with causes known to enhance or degrade intelligibility for a listener, and reports the experimental results obtained with commercial instruments in three acoustic environments.

Correlation of Speech Intelligibility Tests in Reverberant Rooms with Three Predictive Algorithms Kenneth D. Jacob 1020
Subjective intelligibility results for ten variously reverberant rooms are compared with the predictions of three algorithms based on measurements. Experimental details are given to encourage repetition by others. Of the three predictors used here, the Speech Transmission Index was the most accurate.

LETTERS TO THE EDITOR

Comments on "The Analytical Impulse" Eugene T. Patronis, Jr. 1031
Author's Reply Andrew Duncan 1031
Eugene T. Patronis, Jr. Reponse 1032
Andrew Duncan Response 1034

CORRECTIONS

Correction to 1989 September Journal (vol. 37, p. 658) 1034

STANDARDS

Standards News from JASA (Reprint, JASA, Vol. 86(5), p. 2042, 1989 November) 1035

FEATURES

AES 87th Convention Wrap-Up 1042
Program 1056
New AES Officers 1989-1990 1076
1990 AES International Sections Directory 1079

DEPARTMENTS

Review of Acoustical Patents 1036	In Memoriam 1105
News 1040	Call for Papers—AES 87th Convention, Los Angeles, 1990 1106
News of the Sections 1086	Information for Authors of Convention Papers 1108
Upcoming Meetings 1088	Call for Nominations 1109
Sound Track 1090	AES Special Publications 1110
New Products and Developments 1093	AES Conventions and Conferences 1112
Available Literature 1095	
Index to Volume 37 1097	

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 38 NUMBER 1/2

1990 JANUARY/FEBRUARY

CONTENTS

PAPERS

- Authentication of Forensic Audio Recordings** Bruce E. Koenig 3
Taped "fingerprints"—revealing a particular recorder's head structure, transport idiosyncrasies, start and stop transients, and speed defects—assist in identifying a tape as either original or a manipulated copy. The FBI uses these and other laboratory identifications in qualifying recorded evidence for presentation in court.

ENGINEERING REPORTS

- Thermal Parameters and Power Ratings of Loudspeakers** Carlo Zuccatti 34
Voice-coil temperature rise depends on construction specifics of the loudspeaker motor; permissible temperature depends on wire and insulation quality. A typical loudspeaker is analyzed, and formulas are given to determine allowable peak and average power, based on a hypothetical music signal.

COMMUNICATIONS

- Transaural Stereo and Near-Field Listening** Tomas Salava 40
From our current understanding of stereophonic loudspeaker reproduction and room equalization, it appears that a system using dummy-head recordings and near-field loudspeakers might best satisfy the serious listener.

STANDARDS

- Standards News from JASA (Reprint, JASA, Vol. 87(1), pp. 455–456, 1990 January)** 42
Draft AES Recommended Practice for Digital Audio Engineering—Serial Multichannel Audio Digital Interface (MADI) (insert)
Draft AES Recommended Practice for Digital Audio Engineering—Synchronization of Digital Audio Equipment in Studio Operations (insert)

FEATURES

- AES Timeline: The 80s** Stephanie Paynes 49
AES 88th Convention Preview 57
Exhibit Previews 60

DEPARTMENTS

- | | |
|--|---|
| Review of Acoustical Patents 44 | Sound Track 79 |
| News 48 | New Products and Developments 85 |
| News of the Sections 74 | Available Literature 88 |
| Upcoming Meetings 78 | Membership Information 90 |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 38 NUMBER 3

CONTENTS

1990 MARCH

PAPERS

Localization of Sound in a Room with Reflecting Walls W. M. Wagenaars 99
Subjects are tested for ability to discriminate distance and direction of loudspeaker sources in a conventional, reflective living room. Noise, narrow pulses, pulsed sinusoids, and music are the test signals. Discrimination increases with signal bandwidth.

Analysis and Synthesis of Tones by Spectral Interpolation Marie-Helene Serra, Dean Rubine, and Roger Dannenberg 111
A variable instrumental tone is digitally reproduced by interpolating among time-sequential samples of its spectrum. The reproduction proves perceptually indistinguishable from the original even when the acquired spectral samples are relatively infrequent. An elaboration of the method splices the sustained tone with a chosen attack. Results are compared with those of earlier techniques.

A Method of Artificial Reverberation Quality Testing Andrzej Czyzewski 129
Subjective acceptance of early reverberation depends on both the delay time and the music characteristics. The author supposes that reverberation quality might peak at a particular value of the cross-correlation of reverberator input and output signals. Experiments prove the supposition.

ENGINEERING REPORTS

A Generalized Active Equalizer for Closed-Box Loudspeaker Systems W. Marshall Leach, Jr. 142
Provided its resonance frequency and quality factor are known, any closed-box loudspeaker can be equalized to extend its low-frequency response as part of a Butterworth fourth-order alignment. Shown here is the equalizer design for doing so. The method helps to protect the loudspeaker from infrasonic overload and can be modified for other responses of higher order.

LETTERS TO THE EDITOR

Comments on "A Model of Loudspeaker Driver Impedance Incorporating Eddy Currents in the Pole Structure" Edward F. McClain, Jr. 147
Author's Reply John Vanderkooy 147

Comments on "Impulse Measurement of Acoustic Impedance" Keith Holland, Frank Fahy, and Philip Newell 148

Comments on "The Implementation of Recursive Digital Filters for High-Fidelity Audio" Paul E. Neyrinck 149
Author's Reply Jon Dattorro 150

Comments on "The Implementation of Recursive Digital Filters for High-Fidelity Audio" Jon Dattorro 151

CORRECTIONS

Correction to "An Introduction to Band-Pass Loudspeaker Systems" Earl R. Geddes 152

FEATURES

AES 8th International Conference: The Sound of Audio—Preliminary Program..... 156
Fiber Optics—The New Medium for Audio: A Tutorial Ronald G. Ajemian and Albert B. Grundy 160

DEPARTMENTS

Review of Acoustical Patents	153	New Products and Developments	189
News	155	Available Literature	192
News of the Sections	176	In Memoriam	196
Upcoming Meetings	178	AES Special Publications	198
Sound Track	182	AES Conventions and Conferences	200

CONTENTS

INTRODUCTION	Neil A. Shaw	203
--------------------	--------------	-----

PAPERS

Measurement and Estimation of Large Loudspeaker Array Performance Mark R. Gander and John M. Eargle	204
<i>Measurements of small arrays are useful in specifying large arrays, provided low-frequency mutual coupling and large-array distance attenuation are accounted for.</i>	

An Array Filtering Implementation of a Constant-Beam-Width Acoustic Source Jefferson A. Harrell and Elmer L. Hixson	221
<i>Controlling the spacing and frequency response of each element in an array produces a main lobe of nearly constant directivity over a wide band.</i>	

Near-Field and Far-Field Performance of Large Woofer Arrays	G. L. Augspurger	231
<i>Alternatives to the conventional, nondirectional woofer are examined by computer simulation. The near-field stack, tapered endfire array, and cardioid array are practical examples.</i>		

Multiple-Beam, Electronically Steered Line-Source Arrays for Sound-Reinforcement Applications	David G. Meyer	237
<i>An array of horizontal line sources, functionally and esthetically superior to a central cluster, is especially suitable for long, narrow, reverberant environments.</i>		

Prediction of the Full-Space Directivity Characteristics of Loudspeaker Arrays Kenneth D. Jacob and Thomas K. Birkle	250
<i>Five methods for calculating array response are compared, including the detailed responses of individual elements as opposed to assuming element simplicity. A hybrid technique appears to be generally suitable.</i>	

Large Arrays: Measured Free-Field Polar Patterns Compared to a Theoretical Model of a Curved Surface Source	John Meyer and Felicity Seidel	260
<i>The authors propose a definition of loudspeaker arrayability, depending upon whether or not given loudspeaker configurations yield polar irregularities smaller than 6 dB. Measurements illustrate the concept.</i>		

Comparative Performance of Three Types of Directional Devices Used as Concert-Sound Loudspeaker Array Elements	Paul F. Fidlin and David E. Carlson	271
<i>Experimental response patterns are measured for arrays formed of constant-directivity, radial, and collapsing-polar horns. Constant-directivity elements are consistently superior.</i>		

DEPARTMENTS

Review of Acoustical Patents	296	New Products and Developments	314
News of the Sections	298	News	322
Sound Track	306	In Memoriam	324
Upcoming Meetings	310	AES Special Publications	326
AES Conventions and Conferences		328	

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 38 NUMBER 5

1990 MAY

CONTENTS

PAPERS

- Charge Movements on the Stretched Membrane in a Circular Electrostatic Push-Pull Loudspeaker** J. H. Streng 331
Surface movement of an electrostatic diaphragm's charge produces nonlinear distortion and a frequency-dependent change in level. In practice, the distortion can easily be made negligible. Not so the level change.

- Calculation of Sound Radiation from an Unbaffled, Rectangular-Cross-Section Horn Loudspeaker Using Combined Analytical and Boundary-Element Methods** T. Shindo, T. Yoshioka, and K. Fukuyama 340
Computer calculation methods for unbaffled horn radiation are confirmed by measurements on two loudspeakers, large and small.

ENGINEERING REPORTS

- Radiation Impedance Calculations for a Rectangular Piston** G. Bank and J. R. Wright 350
Maxwell suggested a principle for specifying the pressure at each element of a piston in relation to all others. Elaboration of the idea leads to radiation impedance calculations for a rectangular piston of any aspect ratio.

- Telephone Hybrid with an Automatic Dual DSP Feedback Canceled** J. H. M. Janssen and A. M. v. Bokhorst 355
Broadcasts of telephone conversations are spoiled by incomplete cancellation in the conventional telephone hybrid and by send-receive signal mixing in the studio. The resulting voice coloration, feedback, and echo are voided with an automatic digital canceler.

- Audio Applications of Electrothermomechanical Film (ETMF)** Juha Backman 364
A thin plastic film loaded with flat bubbles of air (or liquid) can function as an electroacoustic, electrodynamic, or thermal transducer. Physical properties and possible applications are discussed.

LETTERS TO THE EDITOR

- Comments on "A Digital Approach to Time-Delay Spectrometry"** Robert Bristow-Johnson 372
Author's Reply Richard Greiner 373

STANDARDS

- Standard News from JASA (Reprint JASA, Vol. 87(3), pp. 1374-1376, 1990 March)** 374

FEATURES

- 88th Convention Program** 379
88th Convention Report 386

DEPARTMENTS

- | | |
|---|--|
| Review of Acoustical Patents 377 | New Products and Developments 406 |
| News 394 | In Memoriam 413 |
| News of the Sections 396 | AES Special Publications 414 |
| Sound Track 400 | AES Conventions and Conferences 416 |
| Upcoming Meetings 405 | |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 38 NUMBER 6

1990 June

CONTENTS

PAPERS

Increasing Coverage of International Shortwave Broadcast through Improved Audio Processing Techniques.....Robert Orban 419
Several audio processing methods combine to tailor the modulating signal and increase the average modulation, avoid transmitter distortion, enhance intelligibility, and compensate shortcomings of the usual receiver.

Stereo Reproduction with Good Localization over a Wide Listening Area.....Shigeaki Aoki, Hiroyuki Miyata, and Kiyoshi Sugiyama 433
Each channel of this stereophonic system uses three loudspeakers, separately driven by direct, delayed, and inverted channel signals. Improved localization is demonstrated in a simulated teleconferencing environment.

ENGINEERING REPORTS

An IC Chip Set for 20-Bit A/D Conversion.....Robert W. Adams 440
A technique for analog-to-digital conversion based on noise shaping and digital decimation is realized in integrated circuits and achieves a dynamic range greater than 108 dB. Limiting noise sources are examined.

Measuring AES-EBU Digital Audio Interfaces.....Richard C. Cabot 459
Much equipment is not designed to AES-EBU specification. Even when it is, troubles arise from interference and signal distortion in multiple or mismatched interconnecting cables. Testing methods reveal the problem details.

Dependence of Microphone Pop Data on Loudspeaker Properties.....E. Werner 469
Several loudspeaker pop generators are developed to test microphone response to artificial plosives; recommended loudspeaker excitations are given. Measured pop rankings of the experimental microphones are consistent with subjective results.

FEATURES

8th Conference Program.....479
8th Conference Report.....482
20th Anniversary—European Conventions.....488

DEPARTMENTS

Review of Acoustical Patents477	Available Literature508
News of the Sections494	Call for Papers512
Sound Track499	AES Special Publications518
New Products and Developments503	AES Conventions and Conferences520

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 38 NUMBER 7/8

1990 JULY/AUGUST

CONTENTS

PAPERS

- Theory and Real-Time Implementation of Time-Varying Digital Audio Filters
.....J. N. Mourjopoulos, E. D. Kyriakis-Bitzaros, and C. E. Goutis 523
In-transit signals are corrupted during adjustment of a digital filter's gain or passband. The signal itself, the filter parameters, and parameter rates of change affect the audibility of such disturbances. Optimal conditions for inaudibility are proposed and tested in a microprocessor simulation.

ENGINEERING REPORTS

- The Effects of Sampling Clock Jitter on Nyquist Sampling Analog-to-Digital Converters,
and on Oversampling Delta-Sigma ADCs.....Steven Harris 537
Theory, computer simulation, and experimentally jittered clocks show no difference between Nyquist-sampling and oversampling converter sensitivity to jitter. Peak white-noise jitter must be less than 0.4 nanosecond for a dynamic-range degradation less than 0.5 dB.
- An Improved Stereo Microphone Array Using Boundary Technology: Theoretical Aspects
.....Bruce Bartlett and Michael Billingsley 543
Two omnidirectional microphone capsules, mounted in the angled planes of a baffle, provide a stereophonic microphone that avoids disadvantages of customary arrangements.
- Practical Field Recording Applications: An Improved Stereo Microphone Array
Using Boundary Technology.....Michael Billingsley and Bruce Bartlett 553
The authors summarize several years of experience in recording with a non-traditional microphone, solving difficulties "often impossible to correct" otherwise.
- On the Electroacoustic-Analogous Circuit for a Plane Wave Incident on the Diaphragm of
a Free-Field Pressure Microphone.....W. Marshall Leach, Jr. 566
An improved circuit model for a pressure microphone accounts for reflections at the diaphragm and reveals the characteristic rise in microphone response at high frequency.

FEATURES

- 89th Convention Preview572
Exhibit Previews576
An Afternoon With John G. Frayne597

DEPARTMENTS

- | | |
|--------------------------------------|--|
| Review of Acoustical Patents.....569 | Membership Information.....609 |
| News of the Sections600 | AES Special Publications614 |
| Sound Track606 | AES Conventions and Conferences616 |
| Available Literature608 | |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 38 NUMBER 9

1990 SEPTEMBER

CONTENTS

PAPERS

The PA-422 Communications Interface and Device Control Language Robert L. Rodgers 619
Optimal use of professional, computer-controlled equipment (e.g., equalizers, gain controls) is hampered by lack of an able and flexible communications interface. Hardware, coding, and language for a suitable remedy are detailed here, based on EIA RS-422 specifications.

The Ear as a Mechanism of Communication Edith L.R. Corliss 640
The ear's bandwidth, dynamic range, and signal-to-noise ratio limit satisfactory recognition of speech in much the same way as other communication systems limit reliable information transfer. Speech recognition data assist in the diagnosis of hearing impairments.

A Phase-Linear Audio Equalizer: Design and Implementation 653
..... Juan A. Henriquez, Terry E. Riemer, and Russell E. Trahan, Jr.
An eleven-band digital equalizer permits gain adjustment of each band without affecting others and is phase linear for any gain combination. Design techniques used in the development are useful for other systems.

Investigation of the Nonrigid Behavior of a Loudspeaker Diaphragm Using Modal Analysis 667
..... Christopher J. Struck
Physical distortion of a loudspeaker diaphragm appears at vibration frequencies above the piston range. A loudspeaker's modal analysis is compared with experimental results obtained with a laser velocity transducer.

STANDARDS

Standards News from JASA (Reprint, JASA, Vol. 87(5), pp. 2264-2265, 1990 May) 679
Draft AES Recommended Standard for Sound-Reinforcement Systems—Communications Interface (PA-422) (insert)
Draft AES Standard Method for Digital Audio Engineering—Measurement of Digital Audio Equipment (insert)

FEATURES

Digital Audio Interface Mel Lambert 681

DEPARTMENTS

Review of Acoustical Patents	676	New Products and Developments	708
Forum	680	Available Literature	713
News of the Sections	698	Membership Information	715
Sound Track	704	In Memoriam	718
Upcoming Meetings	706	AES Annual Report	719

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 38 NUMBER 10

1990 OCTOBER

CONTENTS

PAPERS

- Effective Performance of Bessel ArraysD. (Don) B. Keele, Jr. 723
A linear (or square) array of loudspeakers, driven unequally, can produce a directional response identical with that of a single element. Compared with the characteristics of a conventional array, Bessel array efficiency, phase response, and bandwidth prove unexpectedly different.
- An Empirical Model for Loudspeaker Motor ImpedanceJ. R. Wright 749
Four measured parameters define an accurate specification of frequency-dependent voice-coil impedance. Total loudspeaker impedance can then be modeled more precisely to afford a better match with other system components.
- Acoustical Design of Worship SpacesPeter D'Antonio 755
Churches are one example of spaces in which absorption alone is an inadequate tool for acoustic control; proper diffusion of reflections is also required. The author shows examples of these and other environments needing such a combination of techniques.

LETTERS TO THE EDITOR

- Comments on "Chaos, Oversampling, and Noise-Shaping in Digital-to-Analog Conversion"Bob Adams 766
 Author's ReplyM. O. J. Hawksford 767
 More on "Impulse Measurement of Acoustic Impedance"Josef Merhaut 769

FEATURES

- An Afternoon with Harry L. Bryant 773
 Review of Society's Sustaining Members 776

DEPARTMENTS

- | | | | |
|-----------------------------------|-----|------------------------------------|-----|
| Review of Acoustical Patents..... | 770 | New Products and Developments..... | 802 |
| News of the Sections..... | 794 | New Members..... | 810 |
| Sound Track..... | 797 | Available Literature..... | 811 |
| Upcoming Meetings..... | 800 | AES Special Publications..... | 814 |

CONTENTS

PAPERS

Uses and Abuses of the Energy-Time Curve John Vanderkooy and Stanley P. Lipshitz 819
The energy-time curve (ETC) depicts neither energy nor explicit time; its practical interpretation therefore requires unusual care. ETC appearance can be improved—sometimes falsely—when the data are vignettted by a spectral window.

On the Correlation between the Subjective Evaluation of Sound and the Objective Evaluation of Acoustic Parameters for a Selected Source
 Anna Furmann, Edward Hojan, Marek Niewiarowicz, and Piotr Perz 837
An experiment compares measured and subjective evaluations of six dynamic woofers. Consistency and effectiveness of the experimental criteria are tested, including the consistency of the judges. Subjective results relate to the measured initial and terminal transients following a tone burst.

Oversampling Filter Design in Noise-Shaping Digital-to-Analog Conversion
 M.O.J. Hawksford and W. Wingerter 845
Oversampling filters, with and without induced imperfections, are compared by computer simulation. They are practical when partitioned to three or four cascaded stages and are capable of large dynamic range. Dominant system noise usually derives from the (imperfect) DAC itself.

ENGINEERING REPORTS

How Can the Headroom of Digital Records Be Used Optimally?
 Manfred Krause and Holger Petersen 857
Sampled compact discs reveal signal headroom that has not been invaded, presumably for fear of digital clipping. Soft clipping safely exploits several decibels of unused level by inaudibly compressing occasional signal peaks.

STANDARDS

Standards News from JASA (Reprint JASA , Vol. 88(3), pp. 1661–1664, 1990 September) 864

FEATURES

AES Convention Wrap-up: Los Angeles 882
 Program 868
 The New Officers 1990–1991 899

DEPARTMENTS

Forum 867	New Products and Developments 908
News of the Sections 902	Available Literature 917
Sound Track 905	AES Special Publications 918

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 38 NUMBER 12

1990 DECEMBER

CONTENTS

President's Message.....Marshall Buck 923

PAPERS

Oversampled Analog-to-Digital Conversion for Digital Audio Systems
.....Timothy F. Darling and Malcolm O. J. Hawksford 924

Systems using conventional Nyquist-sampled pulse-code modulation resist improvement beyond 16-bit resolution because of defects in practical hardware. The usual shortcomings are evaded with oversampling and noise shaping in a delta-sigma modulation encoder.

Dynamic Measurement and Interpretation of the Nonlinear Parameters of Electrodynamic LoudspeakersWolfgang Klippel 944

Loudspeaker motor and box parameters, variable with diaphragm displacement, are measured dynamically to rank their relative contributions to harmonic and intermodulation distortion. Distortion measurements confirm the calculations.

Evaluation of a Method for Separating Digitized Duet Signals.....Robert C. Maher 956

Two simultaneous musical voices are separated automatically with a method using time-varying analyses of their spectra. Experiments with real and artificial signals identify those signal details that limit the method's subjective success.

LETTERS TO THE EDITOR

Comments on "Comments on 'A Digital Approach to Time-Delay Spectrometry'".....M. A. Poletti 980

Author's Reply.....Robert Bristow-Johnson 980

FEATURES

AES 9th International Conference: Television Sound Today and Tomorrow—
Preliminary Program 986
Index to Volume 38 997
91st Call for Papers 1020
Call for Nominations 1023

DEPARTMENTS

Review of Acoustical Patents.....981	New Products and Developments.....1015
News of the Sections1005	Available Literature1025
Sound Track1010	AES Special Publications1028

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 39 NUMBER 1/2

1991 JANUARY/FEBRUARY

CONTENTS

PAPERS

Principles of Oversampling A/D Conversion	Max W. Hauser	3
<i>Historically, the designers of communications strategies, of integrated circuits, of filter topologies, of automatic controls, have attacked the problems of digital conversion from isolated points of view. Shown here is a more nearly unified picture of analog-digital transformation, with emphasis on the advantages of oversampling.</i>		
Calculation of the Loudness of Loudspeakers during Listening Tests	Ronald M. Aarts	27
<i>Listener-adjusted loudness levels agree well with calculated pink-noise loudness for six loudspeakers. Other program signals show little difference from the pink-noise results. Loudness adjustment based on A-weighting is unreliable.</i>		
Speech Intelligibility in Some German Sports Stadiums	K. Rijk, F. Breuer, and V.M.A. Peutz	39
<i>Eight stadiums were tested for sound-system articulation and for level of sound outside the facility. None were satisfactory. Recommended frequency response, sound pressure levels, and loudspeaker placements are listed for large and small stadiums.</i>		
Design and Measurement of Short Reverberation Times at Low Frequencies in Talks Studios	Birgit Rasmussen, Jens Holger Rindel, and Helge Henriksen	47
<i>Two broadcast studios were designed acoustically to match optimal reverberation times. Analysis of the reverberation measurements with a time-reversed technique reveals low-frequency differences not disclosed by traditional methods.</i>		

FEATURES

Fantasia	66
90th Convention Preview	72
Exhibit Previews	76
91st Call for Papers	104

DEPARTMENTS

Forum	64	Available Literature	100
News of the Sections	93	In Memorium	103
Sound Track	98	AES Special Publications	108
Upcoming Meetings	99		

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 39 NUMBER 3

1991 MARCH

CONTENTS

PAPERS

- Audio Engineering and Psychoacoustics: Matching Signals to the Final Receiver, the Human Auditory System** Eberhard Zwicker and U. Tilmann Zwicker 115
Perceived characteristics of sound are not amplitude, frequency, and time interval—for instance—but loudness, pitch, and subjective duration. All perceived sonic information is contained in a description whose dimensions are specific loudness, critical-band rate, and time. The consequences are important for data-reducing systems.

- Equalization of Loudspeaker Drive Units Considering Both On- and Off-Axis Responses**....Rhonda Wilson 127
Woofers and tweeter impulse data precede the filter design for loudspeaker equalization that corrects on- and off-axis responses simultaneously. Experimental and simulated results are shown for one loudspeaker.

ENGINEERING REPORTS

- On the Advantages of Nested Feedback Loops**.....Jonathan Scott and Graeme Spears 140
Discussion Edward M. Cherry 145
Response Jonathan Scott and Graeme Spears 146
Choice between multiple feedback paths and a single overall feedback loop involves differences in amplifier behavior that may escape the designer's attention. The authors reexamine one of E.M. Cherry's conclusions.

- Harmonic and Intermodulation Performance of Two-Quadrant Bipolar-Transistor Gain Cells** Muhammad Taher Abuelma'atti 148
Distortion components of a multisinusoidal signal are found for a basic amplifier proposed by Hawksford and Mills. A two-frequency example illustrates the theory.

STANDARDS AND INFORMATION DOCUMENTS

- AES Recommended Practice for Digital Audio Engineering—Synchronization of Digital Audio Equipment in Studio Operations**..... 155
- Standards News from JASA (Reprint JASA, Vol. 89(1), pp. 479–483, 1991 January)** 163
- News of the Technical Committees**..... 168
- News of the Standards Committee** 169

FEATURES

- 1991 AES International Sections Directory**..... 175
- 91st Convention, Call for Papers** 203
- 5th Regional Convention, Tokyo, Call for Papers**..... 205
- 3rd Regional Convention, Melbourne, Call for Papers** 207

DEPARTMENTS

- | | | | |
|---|-----|--|-----|
| Review of Acoustical Patents | 171 | New Products and Developments | 193 |
| News of the Sections | 182 | Available Literature | 198 |
| Sound Track | 191 | In Memoriam | 199 |
| Upcoming Meetings | 192 | AES Special Publications | 212 |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 39 NUMBER 4

1991 APRIL

CONTENTS

PAPERS

Nonlinearities in Moving-Coil Loudspeakers with Overhung Voice Coils David R. Birt 219
A loudspeaker's Bl product varies with voice-coil displacement and current. The variation is reduced by improved motor construction and—in these experiments—by active Bl and drive-current corrections.

Accurate Prediction of Speech Intelligibility without the Use of In-Room Measurements Kenneth D. Jacob, Thomas K. Birkle, and Christopher B. Ickler 232
A computed speech transmission index (STI), using a room model, predicts intelligibility without measured room data. No accuracy is lost in substituting the computed STI for one based on in-room measurements. The STI is compared with subjective estimates of intelligibility.

Measurement of Loudspeaker Parameters Using a Laser Velocity Transducer and Two-Channel FFT Analysis Jorge N. Moreno 243
Thiele-Small driver parameters are measured using only a two-channel FFT analyzer and a velocity transducer. No additional test mass or box stiffness is needed, and the same measurements yield diaphragm displacement, driver impedance, and near-field sound pressure.

ENGINEERING REPORTS

Active All-Pass Filters for Audio Robert Orban 250
Detailed comparison of two all-pass filters emphasizes the conflict between apparent circuit simplicity and freedom from the requirement of rigid component tolerances.

LETTERS TO THE EDITOR

Comments on the Distinction between Stereophonic and Binaural Sound Gary C. Eickmeier 261
Authors' Replies: Bruce Bartlett 262
..... Michael Billingsley 263
..... Duane H. Cooper 264
..... Tomas Salava 265

CORRECTIONS

Correction to "Speech Intelligibility in Some German Sports Stadiums" K. Rijk, F. Breuer, and V.M.A. Peutz 266

STANDARDS AND INFORMATION DOCUMENTS

Standards News from JASA (Reprint JASA, Vol. 89(3), pp. 1474-1478, 1991 March) 271
News of the Standards Committee 275
Draft AES Recommended Practice for Professional Audio Equipment—Application of Connectors, Part 1, XLR-Type Polarity and Gender (insert)
Draft AES-ALMA Standard Test Method for Audio Engineering—Measurement of the Lowest Resonance Frequency of Loudspeaker Cones (insert)

FEATURES

9th Conference Report 281
3rd Regional Convention, Melbourne, Call for Papers 278

DEPARTMENTS

Review of Acoustical Patents 267
News of the Sections 286
Sound Track 297
Upcoming Meetings 298
New Products and Developments 300
Available Literature 304
In Memoriam 305
AES Special Publications 308

AES

JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 39 NUMBER 5

1991 MAY

CONTENTS

PAPERS

- Prediction and Measurement of the One-Parameter Behavior of Horns** K. R. Holland, F. J. Fahy, and C. L. Morfey 315
Measurements of throat impedance for various horns agree well with the impedances predicted by a computer model based on Webster's equation. An assumed wavefront geometry is specified adequately by empirical rules.
- Loudspeaker Arrays for Improving Speech Intelligibility in a Reverberant Space** Hiroaki Nomura, Mikio Tohyama, and Tammo Houtgast 338
In a reverberant environment, speech intelligibility improves with a circular array of loudspeakers centered on the listening position. A similar improvement is found for a linear array with individual driver delays.
- Digital Measurement and Comparison of Current-Voltage Output Capability of Amplifiers and Demands of Loudspeakers** Roger C. Fairwood and Martin J. Reed 344
Baxandall's method for matching loudspeaker voltage-current demands with amplifier capability is modified to include digital capture and display of the data. Loudspeaker and amplifier characteristics are clearly and easily compared, as shown in several examples.
- A Comparison of Three Methods of Measuring the Volume Velocity of an Acoustic Source** D. K. Anthony and S. J. Elliott 355
Laser measurements of diaphragm velocity verify the integrity of two constant-volume-velocity sources previously discussed by Salava. Also measured are the source harmonic distortions.

STANDARDS AND INFORMATION DOCUMENTS

- AES Recommended Practice for Digital Audio Engineering—Serial Multichannel Audio Digital Interface (MADI)** 367

FEATURES

- 90th Convention Report: Paris** 390
Program 380

DEPARTMENTS

- | | | | |
|--|-----|--|-----|
| Review of Acoustical Patents | 378 | Available Literature | 417 |
| News of the Sections | 398 | In Memoriam | 419 |
| Upcoming Meetings | 411 | AES Special Publications | 420 |
| Sound Track | 412 | AES Conferences and Conventions | 420 |
| New Products and Developments | 413 | | |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 39 NUMBER 6

1991 JUNE

CONTENTS

PAPERS

Combinatorial Music Theory.....Andrew Duncan 427
"All cows eat grass" might not be recognized, at first, in 100100010010, but chord and scale structures emerge clearly in digital notation. Analytical properties of the diatonic and pentatonic scales appear responsible for their unrivaled musical felicity.

Noise Shaping and Pulse-Width Modulation for an All-Digital Audio Power Amplifier.....J.M. Goldberg and M.B. Sandler 449
Directly converting a digital audio signal to analog power is an alluring idea. Its realization is hastened by combining interpolative noise shaping with a pulse-width-modulation amplifier. Simulations explore several such combinations.

ENGINEERING REPORTS

Effects of Cable, Loudspeaker, and Amplifier InteractionsFred E. Davis 461
Voltage-transfer measurements of twelve loudspeaker cables, linking two amplifiers with two loudspeakers, reveal their mid- and high-frequency differences. Maximum variation at 10 kHz is approximately 0.3 dB.

LETTERS TO THE EDITOR

Comments on "Acoustic Waveguide Theory".....Gavin R. Putland 469
Author's Reply.....Earl R. Geddes 471

STANDARDS AND INFORMATION DOCUMENTS

AES Information Document—Plane-Wave Tubes: Design and Practice 473
Draft AES Recommended Practice for Digital Audio Engineering—Serial Transmission Format for Two-Channel Linearly Represented Digital Audio Data..... (insert)
AES Standards Committee News..... 485

FEATURES

AES 5th Regional Convention: Audio Technologies for the 90s 486
Stereo Broadcasting: A 30-Year Retrospective.....Daniel R. von Recklinghausen 490

DEPARTMENTS

Review of Acoustical Patents481	Available Literature507
News of the Sections496	AES Special Publications508
Sound Track502	Upcoming Meetings511
New Products and Developments504	

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 39 NUMBER 7/8

1991 JULY/AUGUST

CONTENTS

PAPERS

- Theory and Practical Implementation of a Fifth-Order Sigma-Delta A/D Converter**
.....R.W. Adams, P.F. Ferguson, Jr., A. Ganesan, S. Vincelette, A. Volpe, and R. Libert 515
A novel method is shown for designing a stable single-bit, high-order, noise-shaping loop. One result is an 18-bit stereo IC converter with a dynamic range of 105 dB.
- New Factors in Sound for Cinema and Television**.....Tomlinson Holman 529
The theater and the living room require loudspeaker directivities, equalizations, and placements which are similar but differ in detail. Fourteen experiments—and other observations—clarify the differences.
- A Low-Cost End-Fire Acoustic Radiator**.....K.R. Holland and F.J. Fahy 540
An acoustic dual of the shotgun microphone uses a compression driver feeding a pipe lined with holes. Approximate theory yields predictable radiator designs that are particularly suited for reproducing sound in a reverberant space.

ENGINEERING REPORTS

- Computer-Aided Electroacoustic Design with SPICE**.....W. Marshall Leach, Jr. 551
SPICE program software easily models electrical and electromechanical elements, thereby assisting in the analysis and design of circuits, microphones, and loudspeakers. The author shows how.

STANDARDS AND INFORMATION DOCUMENTS

- Draft AES Recommended Practice for Digital Audio Engineering—Format for the User
Data Channel of the AES Digital Audio Interface**..... (insert)
- AES Standards Committee News**..... 568

FEATURES

- 92nd AES Convention, Austria Call for Papers**..... 590
- AES 3rd Regional Convention: Audio Automation Future Directions**..... 598

DEPARTMENTS

- | | | | |
|---|-----|--|-----|
| Review of Acoustical Patents | 564 | New Products and Developments | 583 |
| News of the Sections | 570 | AES Annual Report | 589 |
| Sound Track | 580 | In Memoriam | 593 |
| Upcoming Meetings | 582 | AES Special Publications | 594 |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 39 NUMBER 9

1991 SEPTEMBER

CONTENTS

President's Message: New Editors.....	Marshall Buck	603
PAPERS		
A Computer Model of Binaural Localization for Stereo Imaging Measurement	Ewan A. Macpherson	604
<i>A computer program, modeled on the behavior of the inner ear, operates on data received from a dummy-head microphone. The computer localizations of various sound sources agree at least qualitatively with those of live listeners.</i>		
Room-Related Balancing Technique: A Method for Optimizing Recording Quality	Martin Wöhr, Günther Theile, Hans-Jürgen Goeres, and Alexander Persterer	623
<i>Conventional stereophonic reproduction fails to produce an adequate impression of depth. Imaging information is degraded if spot microphone signals are mixed directly with outputs of the main (stereo) pair. Improved image quality is achieved by processing spot microphone signals to generate artificial reflections which incorporate the effects of the room boundaries.</i>		
An Intuitive View of Coincident Stereo Microphones	Stephen Julstrom	632
<i>The author reviews the directionalities of stereophonic microphone pairs. Polar diagrams in three dimensions, in contrast with the familiar equatorial-plane response, remind that sensitivities to sources above, beside, and behind the microphone constitute the important differences among them.</i>		
ENGINEERING REPORTS		
A Class D Amplifier Using MOSFETs with Reduced Minority Carrier Lifetime	Jon Hancock	650
<i>Circuit choices are given for the modulator, output filter, and power supply serving a 0.5-MHz pulse-width modulation converter. Careful design protects the MOSFET switches during commutation and reverse recovery.</i>		
STANDARDS AND INFORMATION DOCUMENTS		
AES Recommended Practice for Sound-Reinforcement Systems—Communications Interface (PA-422)		663
AES Standards Committee News		680
FEATURES		
AES 91st Convention Preview		682
Calendar		684
Exhibitor List		686
Exhibit Previews		690
DEPARTMENTS		
News of the Sections	720	
Available Literature	727	
Upcoming Meetings	730	
Membership Information		730
In Memoriam		735
AES Conventions and Conferences		736

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 39 NUMBER 10

1991 OCTOBER

CONTENTS

PAPERS

- Efficient Filter Design for Loudspeaker Equalization** Richard Greenfield and Malcolm Omar Hawksford 739
Digital filters offer the opportunity to improve a loudspeaker's amplitude and phase responses simultaneously. This paper compares FIR and IIR structures for doing so, outlines a rationale for filter design, and identifies other applications for the technique.
- Measurement of Panel Reflection Using Acoustical Scale Modeling Techniques** Jose C. Ortega 752
Modeling reveals the reflective differences among plane, curved, and segmented acoustic panels. For wideband uniformity, panel dimensions must exceed the largest working wavelength. Edge diffractions may spoil the performance.
- On the Naturalness of Two-Channel Stereo Sound** Günther Theile 761
For two-channel stereophonic reproduction, the projected image is, at best, a two-dimensional image (of three-dimensional sound space) in the plane that includes the loudspeakers. This nevertheless natural result is conveniently achieved with the outputs of a sphere microphone, augmented by delayed and processed spot-microphone signals.

ENGINEERING REPORTS

- Making Recordings for Simulation Tests in the Archimedes Project** Villy Hansen and Gert Munch 768
Archimedes aims to measure the subjective effects of listening room acoustics and loudspeaker directivities. Controlled experiments need carefully defined and repeatable program material. Shown here are the program specifications and recording procedures.
- The Operational Voltage-Controlled Element: Generalizing the VCA** Douglas Frey 775
A versatile monolithic device performs as a voltage-controlled amplifier, a voltage-controlled potentiometer, or an operational amplifier in circuit configurations that require otherwise separate equivalents. Applications are suggested, with assessment of noise and distortion behavior.

CORRECTIONS

- Corrections to "Combinatorial Music Theory" Andrew Duncan 784

STANDARDS AND INFORMATION DOCUMENTS

- AES Standards Committee News 785

FEATURES

- Review of Society's Sustaining Members 790

DEPARTMENTS

- | | |
|---|---|
| Review of Acoustical Patents 786 | Available Literature 823 |
| News of the Sections 810 | Membership Information 825 |
| Upcoming Meetings 816 | In Memoriam 827 |
| Sound Track 817 | AES Special Publications 829 |
| New Products and Developments 820 | AES Conventions and Conferences 832 |

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 39 NUMBER 11

1991 NOVEMBER

CONTENTS

President's Message Roger K. Furness 835

PAPERS

Minimally Audible Noise Shaping Stanley P. Lipshitz, John Vanderkooy, and Robert A. Wannamaker 836
The perceptibility of requantizing noise is minimized by designing the noise shaper "to approximate the inverse of the audibility curve." Relatively simple techniques provide a signal-to-noise improvement equivalent to an additional two bits; greater improvement is bought with increased complexity.

ENGINEERING REPORTS

Low-Frequency Performance of Listening Rooms for Steady-State and Transient Signals Tomas Salava 853
A loudspeaker's free-field response does not predict its particular performance in a room whose dimensions are comparable with the acoustic wavelength. Loudspeaker-room coupling is described conveniently with two impedance models, and several examples are shown. Listeners test their recognition of low-frequency response irregularities.

Challenges to the Successful Implementation of 3-D Sound Durand R. Begault 864
Creative audio producers now use filtering techniques based on the head-related transfer function, but these techniques are only partial answers to problems in 3-D listener localization. A satisfactory 3-D system awaits future psychoacoustic research.

A Monolithic Dual Switch for Professional Audio Applications Derek F. Bowers 871
A dual integrated-circuit switch, each section structured as a T of junction FETs, achieves 120 dB of OFF attenuation, very low ON distortion, low crosstalk, and negligible control-signal feedthrough.

COMMUNICATIONS

Corrigendum: To the Gap Loss Formula, the Asymptotic Expansion (Eq. 15a) of Westmijze's "Studies on Magnetic Recording" [1] John G. (Jay) McKnight 878
A correction and the explanation of it are given for Westmijze's formula specifying gap loss in magnetic tape reproduction.

FEATURES

5th Regional Convention Report, Tokyo 882
 6th Regional Convention Report, Melbourne, Australia 886
 10th International Conference Report, London 892
 New AES Officers 1991/1992 898
 11th International Conference, Portland, Oregon, Call for Papers 918

DEPARTMENTS

Review of Acoustical Patents 879	Available Literature 914
News of the Sections 904	Upcoming Meetings 916
Sound Track 909	Membership Information 917
New Products and Developments 912	AES Conventions and Conferences 920

AES JOURNAL OF THE AUDIO ENGINEERING SOCIETY AUDIO/ACOUSTICS/APPLICATIONS

VOLUME 39 NUMBER 12

1991 DECEMBER

CONTENTS

PAPERS

- A Simple Theory of Cabinet Edge Diffraction**John Vanderkooy 923
Cabinet edge diffraction is shown to be stronger than had been predicted by earlier theory and strongly dependent on observation angle. Its computer analysis is fast and efficient. Model results are compared with those of others.
- A Method for Envelope Warping in Digital Audio Synthesis**Robert C. Maher 934
Nonlinear table-lookup rates permit stored sections of musical envelopes to be stretched, or contracted, without injecting timbral discontinuities. Computer simulation demonstrates the technique.
- Acoustic Wave Action Inside Rectangular Loudspeaker Cabinets**Jeong-Guon Ih 945
Low-frequency driver-enclosure interaction is analyzed for a non-absorbent, rectangular box with drivers or vents at various locations on the box surface. Mass loading varies substantially with driver position.

ENGINEERING REPORTS

- Reliable Detection of Acoustically Coupled DTMF Signals**James H. Hahn 956
Decoding of dual-tone multifrequency (DTMF) signals is unreliable when the signals are coupled acoustically to the telephone transmitter. Analog processing at the tone receiver reduces error that would otherwise arise from unavoidable distortion.

STANDARDS AND INFORMATION DOCUMENTS

- AES standard method for digital audio engineering—Measurement of digital audio equipment** 961
AES Standards Committee News 976

FEATURES

- 91st Convention Report** 978
Exhibitors 988
Program 992
1991/1992 AES International Sections Directory 1018
Call for Awards Nominations 1040
Index to Volume 39 1048

ARTICLES

- The Ethics of Preservation, Restoration, and Re-Issues of Historical Sound Recordings**Dietrich Schüller 1014
Technical or artistic alteration of original recordings, whether for purposes of preservation or re-issue, must be carefully and openly documented in all of its details.

DEPARTMENTS

- | | |
|--|---|
| News of the Sections 1032 | New Products and Developments 1042 |
| Upcoming Meetings 1038 | Membership Information 1045 |
| Sound Track 1039 | In Memoriam 1047 |
| Available Literature 1041 | AES Conventions and Conferences 1056 |