STANDARDS AND AES3-2-2009 (reaffirmed 2019) INFORMATION DOCUMENTS



AES standard for digital audio —
Digital input-output interfacing —
Serial transmission format for two-channel
linearly represented digital audio data
Part 2: Metadata and Subcode

(Multi-part revision of AES3-2003, incorporating Amendments 5 & 6)

Users of this standard are encouraged to determine if they are using the latest printing incorporating all current amendments and editorial corrections. Information on the latest status, edition, and printing of a standard can be found at: http://www.aes.org/standards

AUDIO ENGINEERING SOCIETY, INC.

551 Fifth Avenue, Room 1225, New York, NY 10176. US.

Document preview: for full document, go to www.aes.org/publications/standards



The AES Standards Committee is the organization responsible for the standards program of the Audio Engineering Society. It publishes technical standards, information documents and technical reports. Working groups and task groups with a fully international membership are engaged in writing standards covering fields that include topics of specific relevance to professional audio. Membership of any AES standards working group is open to all individuals who are materially and directly affected by the documents that may be issued under the scope of that working group.

Complete information, including working group scopes and project status is available at http://www.aes.org/standards. Enquiries may be addressed to standards@aes.org

The AES Standards Committee is supported in part by those listed below who, as Standards Sustainers, make significant financial contribution to its operation.





Focusrite[®]
























































































This list is current as of 2018/9/01

AES standard for digital audio — Digital input-output interfacing — Serial transmission format for two-channel linearly-represented digital audio data — Part 2: Metadata and Subcode

Published by **Audio Engineering Society, Inc.**Copyright ©2009 by the Audio Engineering Society

Abstract

AES3 provides for the serial digital transmission of two channels of periodically sampled and uniformly quantized audio signals on various media.

This Part specifies the information transmitted with the audio data: principally the "channel status" but also user data and the use of the auxiliary bits to carry a co-ordination signal.

An AES standard implies a consensus of those directly and materially affected by its scope and provisions and is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an AES standard does not in any respect preclude anyone, whether or not he or she has approved the document, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in agreement with the standard. Prior to approval, all parties were provided opportunities to comment or object to any provision. Attention is drawn to the possibility that some of the elements of this AES standard or information document may be the subject of patent rights. AES shall not be held responsible for identifying any or all such patents. Approval does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the standards document. This document is subject to periodic review and users are cautioned to obtain the latest edition. Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Contents

1 Scope	4
2 Normative references	4
3 Definitions and abbreviations	5
4 User data format	5
5 Channel status format	5
5.1 Channel status bit	5
5.2 Channel status block	6
5.3 Implementation	
5.3.1 Implementation levels	
5.3.1.2 Standard Level	6
5.3.1.3 Enhanced Level	
5.3.2 Transmitter requirement	6
5.3.3 Receiver requirement	
5.4 Documentation	
5.5 Channel status content	
5.5.0 Byte 0: Basic audio parameters	
5.5.1 Byte 1: Channel modes, user bits management	
5.5.2 Byte 2: Auxiliary bits, word length and alignment level	
5.5.3 Byte 3: Multichannel modes	
5.5.4 Byte 4: DARS, hidden information, multiple-rate sampling frequencies	
5.5.5 Byte 5: Reserved	
5.5.6 Bytes 6 to 9: Alphanumeric channel origin	
5.5.7 Bytes 10 to 13: Alphanumeric channel destination	
5.5.8 Bytes 14 to 17: Local sample address code	
5.5.9 Bytes 18 to 21: Time-of-day sample address code	
5.5.10 Byte 22: Reserved	
5.5.11 Byte 23: Channel status data CRCC	
5.6 Channel Status when non-PCM audio is flagged	
6. Auxiliary bits	
6.1 Availability of auxiliary bits	14
6.2 Use of auxiliary bits	14
Annex A (informative) Informative references	15
Annex B (informative) Provision of additional, voice-quality channels	16
Annex C (informative) Generation of CRCC (byte 23) for channel status	17

Foreword

This foreword is not part of the AES3-2-2009, AES standard for digital audio — Digital input-output interfacing — Serial transmission format for two-channel linearly represented digital audio data, Part 2: Metadata and Subcode

AES3 has been under constant review since the standard was first issued in 1985, and the present edition reflects the collective experience and opinions of many users, manufacturers, and organizations familiar with equipment or systems employing AES3.

This document was adapted by R. Caine from the 2003 edition as amended by Amendments 5 and 6, and its technical content is believed to be identical to the relevant parts of that version. Other members of the writing group that developed this document in draft included: C. Travis, C. Langen, H. Jahne, J. Grant, J. Woodgate, M. Natter, M. Poimboeuf, R. Cabot, S. Heinzmann, M. Werwein, and M. Yonge.

J Grant, chair SC-02-02 Working Group on Digital Input-Output Interfacing May 2009

Note on normative language

In AES standards documents, sentences containing the word "shall" are requirements for compliance with the document. Sentences containing the verb "should" are strong suggestions (recommendations). Sentences giving permission use the verb "may". Sentences expressing a possibility use the verb "can".

AES standard for digital audio — Digital input-output interfacing — Serial transmission format for two-channel linearly-represented digital audio data — Part 2: Metadata and Subcode

1 Scope

These four documents specify an interface for the serial digital transmission of two channels of periodically sampled and linearly represented digital audio data from one transmitter to one receiver. This Part 2 defines the format for coding metadata, or subcode, relating to the audio content and carried with it.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this document. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this document are encouraged to investigate the possibility of applying the most recent editions of the indicated standards.

AES18, AES recommended practice for digital audio engineering—Format for the user data channel of the AES digital audio interface, Audio Engineering Society, New York, NY, USA.

AES52-2006: AES standard for digital audio engineering — Insertion of unique identifiers into the AES3 transport stream, Audio Engineering Society, New York, NY, USA.

IEC 60958-3 *Digital audio interface - Part 3: Consumer applications*, International Electrotechnical Commission, Geneva, Switzerland.

ISO 646, *Information processing—ISO 7-bit coded character set for information interchange*, International Organization for Standardization, Geneva, Switzerland.

ITU-R BS.450 Transmission standards for FM sound broadcasting at VHF International Telecommunication Union, Geneva, Switzerland. (was CCIR Rec 450-1),

ITU-T J.17, Pre-emphasis used on sound program circuits, International Telecommunication Union, Geneva, Switzerland..