# STANDARDS AND AES66-2012 (r2023) INFORMATION DOCUMENTS



AES standard for professional audio equipment - Application of connectors - Miniature XLR-type polarity and gender

Users of this standard are encouraged to determine if they are using the latest printing incorporating all current amendments and editorial corrections. Information on the latest status, edition, and printing of a standard can be found at: http://www.aes.org/standards

**AUDIO ENGINEERING SOCIETY, INC.** 

697 Third Ave., Suite 405, New York, New York 10017, US.



The AES Standards Committee is the organization responsible for the standards program of the Audio Engineering Society. It publishes technical standards, information documents and technical reports. Working groups and task groups with a fully international membership are engaged in writing standards covering fields that include topics of specific relevance to professional audio. Membership of any AES standards working group is open to all individuals who are materially and directly affected by the documents that may be issued under the scope of that working group.

Complete information, including working group scopes and project status is available at http://www.aes.org/standards. Enquiries may be addressed to standards@aes.org

The AES Standards Committee is supported in part by those listed below who, as Standards Sustainers, make significant financial contribution to its operation.



### **DOLBY.** Focusrite


































































## AES standard for professional audio equipment - Application of connectors - Miniature XLR-type polarity and gender

Published by

Audio Engineering Society, Inc.

Copyright © 2012, 2018, 2023 by the Audio Engineering Society

### **Abstract**

This standard is intended to apply to three- and five-pin circular connectors, commonly and generically known as miniature XLR-type, used for the balanced interconnection of all categories of sound system components for professional audio, commercial, recording, broadcast, and similar applications, regardless of function, type, or level of the signal. It specifies the application and polarity of analog signals for these connectors and is intended to avoid the inversion of absolute polarity among the items in the analog signal chain.

An AES standard implies a consensus of those directly and materially affected by its scope and provisions and is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an AES standard does not in any respect preclude anyone, whether or not he or she has approved the document, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in agreement with the Standard. Prior to approval, all parties were provided opportunities to comment or object to any provision. Attention is drawn to the possibility that some of the elements of this AES standard or information document may be the subject of patent rights. AES shall not be held responsible for identifying any or all such patents. Approval does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the standards document. This document is subject to periodic review and users are cautioned to obtain the latest edition. Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

### **Contents**

Foreword	3
Introduction	4
1 Scope	4
2 Normative references	4
3 Definitions	
4 Connector usage	5 5
Annex A Bibliography	

### **Foreword**

This Foreword is not a part of the AES66-2012 AES standard for professional audio equipment - Application of connectors - Miniature XLR-type polarity and gender.

In 1992, after many years of confusion in the absence of a polarity standard for balanced audio over XR connectors, the AES first published AES14, AES standard for professional audio equipment - Application of connectors, part 1, XLR-type polarity and gender. Largely as a result of this, XLR usage in the field has become substantially stable and interoperable to the extent that equipment and XLR cables are routinely connected together correctly without surprise or dismay.

The later introduction of miniature XLR connectors, increasingly used to economize on panel space in compact equipment, prompted a revisit of this area. Miniature XLR connectors, sometimes called "tiny XLR", have a different pin-numbering scheme, and a different keyway, however the need for predictable standard for gender and polarity remains necessary for professional applications.

The AES Standards Working Group SC-05-02 on Audio Connectors developed this standard under project AES-X205.

Ray Rayburn Chair, SC-05-02 Working Group on Audio Connectors 2012-12-18

### Note on normative language

In AES standards documents, sentences containing the word "shall" are requirements for compliance with the document. Sentences containing the verb "should" are strong suggestions (recommendations). Sentences giving permission use the verb "may". Sentences expressing a possibility use the verb "can".

### AES standard for professional audio equipment - Application of connectors - Miniature XLR-type, polarity and gender

### Introduction

In sound systems it is often necessary to connect pieces of equipment from different manufacturers. This standard provides a common scheme for wiring the connectors used - particularly to avoid the inversion of absolute polarity among the items in a signal chain. Consistent usage regarding positive-polarity and return terminals will also provide more stable interoperability when balanced and unbalanced interfaces are combined.

### 1 Scope

This standard shall apply to three- and five-pin circular connectors, commonly and generically known as miniature XLR-type, used for the balanced interconnection of all categories of sound system components for professional audio, commercial, recording, broadcast, and similar applications, regardless of function, type, or level of the signal. It specifies the application and polarity of analog signals for these connectors. This standard does not pertain to the dimensions of the connectors.

NOTE - Use of this connector may be restricted by safety regulations.

### 2 Normative references

No normative references are required to implement this standard.

### 3 Definitions

### 3.1

### Positive sound pressure

shall designate that portion of the sound wave during which the pressure is in excess of the atmospheric ambient.

### 3.2

### Positive polarity

shall designate an electrical signal voltage which acquires a potential that has a phase angle within 90 degrees with respect to a positive sound pressure peak.

### 3.3

### Positive-polarity terminal

shall be that terminal on which a positive signal shall be measured with respect to the oppositely polarized terminal when a positive-polarity signal is applied as observed with an oscilloscope or similarly functioning instrument.

### 3.4

### **Return terminal**

shall be that terminal which is polarized opposite to the positive-polarity terminal, that is, the negative-polarity terminal.