AES standard for digital audio — Digital input-output interfacing — Serial transmission format for two-channel linearly-represented digital audio data — Part 3: Transport

Published by **Audio Engineering Society, Inc.**Copyright ©2009 by the Audio Engineering Society

Abstract

AES3 provides for the serial digital transmission of two channels of periodically sampled and uniformly quantized audio signals on various media.

This Part specifies the framing and channel coding for transmission on a unidirectional point-to-point physical link. The specified format minimizes the direct-current (DC) component on the transmission line, facilitates clock recovery from the data stream, and makes the interface insensitive to the polarity of connections.

An AES standard implies a consensus of those directly and materially affected by its scope and provisions and is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an AES standard does not in any respect preclude anyone, whether or not he or she has approved the document, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in agreement with the standard. Prior to approval, all parties were provided opportunities to comment or object to any provision. Attention is drawn to the possibility that some of the elements of this AES standard or information document may be the subject of patent rights. AES shall not be held responsible for identifying any or all such patents. Approval does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the standards document. This document is subject to periodic review and users are cautioned to obtain the latest edition. Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Document preview: for full document, go to www.aes.org/publications/standards

Contents

1 Scope	4
2 Normative references	4
3 Definitions and abbreviations	
4 Subframe	
4.1 Subframe time slots	
4.2 Preambles	
4.3 Audio data content	
4.4 Sample word orientation	
4.5 MSB position	6
4.6 Validity bit	6
4.7 User data bit	6
4.8 Channel status bit	
4.9 Parity bit	6
5 Frame	7
6 Channel coding (line coding)	8
7. Preambles	و
7.1 Preamble time slots	
7.2 First subframe preamble	
7.3 Second subframe preamble	
7.4 Preamble codes	
8. Block	10
Annex Δ (informative) Informative references	

Foreword

This foreword is not part of the AES3-3-2009, AES standard for digital audio — Digital input-output interfacing — Serial transmission format for two-channel linearly represented digital audio data, Part 3: Transport.

AES3 has been under constant review since the standard was first issued in 1985, and the present edition reflects the collective experience and opinions of many users, manufacturers, and organizations familiar with equipment or systems employing AES3.

This document was adapted by R. Caine from the 2003 edition as amended by Amendments 5 and 6, and its technical content is believed to be identical to the relevant parts of that version. Other members of the writing group that developed this document in draft included: C. Travis, C. Langen, H. Jahne, J. Grant, J. Woodgate, M. Natter, M. Poimboeuf, R. Cabot, S. Heinzmann, M. Werwein, and M. Yonge.

J Grant, chair SC-02-02 Working Group on Digital Input-Output Interfacing May 2009

Note on normative language

In AES standards documents, sentences containing the word "shall" are requirements for compliance with the document. Sentences containing the verb "should" are strong suggestions (recommendations). Sentences giving permission use the verb "may". Sentences expressing a possibility use the verb "can".

Document preview: for full document, go to www.aes.org/publications/standards

AES standard for digital audio — Digital input-output interfacing — Serial transmission format for two-channel linearly-represented digital audio data — Part 3: Transport

1 Scope

These four documents specify an interface for the serial digital transmission of two channels of periodically sampled and linearly represented digital audio data from one transmitter to one receiver. This Part 3 defines the format for transport of an AES3 digital audio interface.

Specific synchronization issues are covered in AES11 AES recommended practice for digital audio engineering -- Synchronization of digital audio equipment in studio operations. An engineering guideline document to accompany this interface specification has been published as AES-2id AES information document for digital audio engineering - Guidelines for the use of the AES3 interface.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this document. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this document are encouraged to investigate the possibility of applying the most recent editions of the indicated standards.

None.

Document preview: for full document, go to www.aes.org/publications/standards