

AES standard for digital audio – Digital input-output interfacing – Sample-accurate timing in AES47

Published by
Audio Engineering Society, Inc.
Copyright ©2006 by the Audio Engineering Society

Abstract

This document specifies how the timing markers specified in AES47 may be used to associate an absolute timestamp with individual audio samples. AES47 specifies a format for the transmission of digital audio over asynchronous transfer mode (ATM) networks. A recommendation is made to refer these timestamps to the SMPTE epoch which in turn provides a reference to UTC and GPS time.

An AES standard implies a consensus of those directly and materially affected by its scope and provisions and is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an AES standard does not in any respect preclude anyone, whether or not he or she has approved the document, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in agreement with the standard. Prior to approval, all parties were provided opportunities to comment or object to any provision. Attention is drawn to the possibility that some of the elements of this AES standard or information document may be the subject of patent rights. AES shall not be held responsible for identifying any or all such patents. Approval does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the standards document. This document is subject to periodic review and users are cautioned to obtain the latest edition. Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Document preview:
for full document, go to
www.aes.org/publications/standards

Contents

0 Preamble	4
0.1 Patents	4
1 Scope	4
2 Normative references	4
3 Definitions and abbreviations	5
4 Numbering of samples	5
5 Numbering of cells	5
6 Sequence numbers and blocks	6
Annex A: Background information	7
A.1 Choice of origin of sample numbering	7
A.2 Calculation of sample number	7
A.3 Local clock ticks	7

Foreword

This foreword is not part of AES53-2006 *AES standard for digital audio - Digital input-output interfacing - Sample-accurate timing in AES47*

This document was prepared by J. Grant for working group SC-02-02, under project AES-X148, "Sample-accurate timing in AES47". The task group members included K. Brown, R. Caine, C. Chambers, P. Eastty, C. Gaunt, K. Gross, U. Horbach, H. Lemcke, M. Page, M. Schindele, J. Strawn, T. Thompson, J. Waas, and M. Yonge.

Preview only
www.aes.org/standards

Note on normative language

In AES standards documents, sentences containing the word "shall" are requirements for compliance with the document. Sentences containing the verb "should" are strong suggestions (recommendations). Sentences giving permission use the verb "may". Sentences expressing a possibility use the verb "can".

Document preview:
for full document, go to
www.aes.org/publications/standards

AES standard for digital audio — Digital input-output interfacing — Sample-accurate timing in AES47

Introduction

This document provides a standard way of identifying the time to which each sample in an AES47 audio stream relates.

It thus provides a way of aligning streams from disparate sources, including synchronizing audio to video, and also allows the total delay across a network to be controlled when the transit time of individual cells is unknown.

This is most effective in systems where the audio is aligned with an absolute time reference such as GPS, but can also be used with a local reference.

The identification repeats every 16 seconds if sequence numbers are used in the AES47 stream, 1 second if only the "ATM user to ATM user indication" (UI) bit in the cell header is used. If absolute time can be distributed by a means outside the scope of this standard (see, for example, 4.4 and A.4.4 of AES51-2006), absolute timestamps can be associated with all audio samples.

0 Preamble

0.1 Patents

Attention is drawn to the possibility that some of the elements of this AES standard may be the subject of patent rights other than those identified herein. AES shall not be held responsible for identifying any or all such patent rights.

1 Scope

This standard specifies how the timing markers specified in 4.1.4.1.1 and 4.5 of AES47 may be used to associate an absolute timestamp with individual audio samples.

It does not specify how the recipient of a call is informed whether the timing markers will conform to this standard or merely meet the minimum specifications laid down in AES47.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

AES47: *AES standard for digital audio — Digital input-output interfacing — Transmission of digital audio over asynchronous transfer mode (ATM) networks*: Audio Engineering Society, New York, NY., US. 2002, 2006

SMPTE 404M: *SMPTE standard for television, audio, and film - SMPTE Epoch*, Society of Motion Picture and Television Engineers, White Plains, NY., US.

Document preview:
for full document, go to
www.aes.org/publications/standards