STANDARDS AND INFORMATION DOCUMENTS

AUDIO

A

ES

®

STANDARDS

AES standard on digital audio – File format for transferring digital audio data between systems of different type and manufacture

Users of this standard are encouraged to determine if they are using the latest printing incorporating all current amendments and editorial corrections. Information on the latest status, edition, and printing of a standard can be found at: http://www.aes.org/standards

The AES Standards Committee is the organization responsible for the standards program of the Audio Engineering Society. It publishes technical standards, information documents and technical reports. Working groups and task groups with a fully international membership are engaged in writing standards covering fields that include topics of specific relevance to professional audio. Membership of any AES standards working group is open to all individuals who are materially and directly affected by the documents that may be issued under the scope of that working group.

Complete information, including working group scopes and project status is available at http://www.aes.org/standards. Enquiries may be addressed to standards@aes.org

The AES Standards Committee is supported in part by those listed below who, as Standards Sustainers, make significant financial contribution to its operation.

This list is current as of 2019/6/30

AES standard on digital audio – File format for transferring digital audio data between systems of different type and manufacture

Published by
Audio Engineering Society, Inc.
Copyright © 2012, 2019 by the Audio Engineering Society

Abstract

The Broadcast Wave Format is a file format for audio data. It can be used for the seamless exchange of audio material between (i) different broadcast environments and (ii) equipment based on different computer platforms.

As well as the audio data, a BWF file (BWFF) contains the minimum information - or metadata - that is considered necessary for all broadcast applications. The Broadcast Wave Format is based on the Microsoft WAVE audio file format. This specification adds a "Broadcast Audio Extension" chunk to the basic WAVE format.

An optional Extended Broadcast Wave Format (BWF-E) file format is designed to be a compatible extension of the Broadcast Wave Format (BWF) for audio file sizes larger than a conventional Wave file. It extends the maximum size capabilities of the RIFF/WAVE format by increasing its address space to 64 bits where necessary. A set of machine-readable loudness metadata is included.

This revision includes a new annex I to describe a universal 'ubxt' chunk to carry human-readable information in UTF-8 multi-byte characters to support international character sets. This is compatible with EBU v2 broadcast wave files.

Audio Engineering Society Inc. 551 Fifth Avenue, Room 1225, New York, NY 10176, US.
www.aes.org/standards   standards@aes.org.

2019-5-22 printing

Contents

Foreword

[This foreword is not part of the AES31-2 *Standard on network and file transfer of audio – Audio-file transfer and exchange – File format for transferring digital audio data between systems of different type and manufacture*.]

This document was produced by a writing group of the SC-02-08 Working Group on Audio-File Transfer and Exchange of the SC-02 Subcommittee on Digital Audio under project AES-X066. Contributors to this project included: D. Ackerman, S. Aoki, I. Beynon, D. Brenan, J. Bull, R. Chalmers, B. Devlin, J. Emmett, A. Faust, C. Garza, Y. Grabit, U. Henry, A. Holzinger, P. Jessop, H. Nakashima, M. Yonge, J. Yoshio.

M. Yonge, chair
B. Harris, vice-chair

SC-02-08 Working Group on Audio-File Transfer and Exchange
2006-03-25

Foreword to 2012 edition

This revision incorporates AES31-2 Am.1 2008, *Amendment 1 to AES31-2 - Audio-file transfer and exchange - Part 2: File format for transferring digital audio data between systems of different type and manufacture - Extended file format for audio to exceed 4 GByte* as annex F.

This revision also introduces a means to carry loudness metadata related to the audio content. These files are identified as version 2 and are both forwards and backwards compatible with version 1 files and implementations.

M. Yonge, chair SC-02-08 Working Group on Audio-File Transfer and Exchange
2012-11-19

Foreword to 2019 edition

This revision includes a new annex I to describe a universal 'ubxt' chunk to carry human-readable information in UTF-8 multi-byte characters to support international character sets. The 'ubxt' chunk is always in addition to the basic 'bext' chunk and never used on its own. The document also specifies requirements for implementation, and priority of data when the machine-readable elements in the 'bext' and 'ubxt' chunks are not identical. This revision is intended to be compatible with IEC 62942, currently in development.

This revision replaces and supersedes AES31-2-2012.

M. Yonge, chair SC-02-08 Working Group on Audio-File Transfer and Exchange
2019-02-23

Note on normative language

In AES standards documents, sentences containing the word "shall" are requirements for compliance with the document. Sentences containing the verb "should" are strong suggestions (recommendations). Sentences giving permission use the verb "may". Sentences expressing a possibility use the verb "can".

AES standard on digital audio – File format for transferring digital audio data between systems of different type and manufacture

0 Introduction

0.1 General

The broadcast-wave-format file (BWFF) is based on the Microsoft Wave audio file format, which is a type of file specified in the Microsoft resource interchange file format (RIFF). Wave files specifically contain audio data. The basic building block of a RIFF file is a chunk which contains specific information, an identification field, and a size field. A RIFF file contains a number of chunks.

The BWFF specifically includes a <Broadcast Audio Extension> chunk to carry certain metadata important for broadcast and professional use. For reliable interchange, some restrictions apply to the format of the audio data.

The Broadcast Wave Format was first developed using ASCII text for all fields. Later, as the format was further developed, it was proposed to use multi-byte characters to internationalize the format. It was understood that to use multi-byte character sets within the existing format would cause compatibility issues when multi-byte metadata was parsed by applications expecting ASCII text. The separate nature of human-readable and machine-readable metadata was established, and a new "universal" chunk was established to carry internationalized human-readable metadata using multi-byte character sets without interoperability issues. This is described in annex I.

This document contains the specification of the broadcast audio extension chunk and its use with PCM-coded audio data. Basic information on the RIFF format and how it can be extended to other types of audio data is given in annex A and annex F. Details of the PCM Wave format are also given in annex A.

0.2 Data types

The following mnemonics describe the data types used throughout this document. Multi-byte data types are little-endian:

Data Type	Meaning	Equiv. C type
CHAR	8-bit signed integer, representing integer values from –128 to +127	signed char
BYTE	8 bit unsigned integer, representing integer values from 0 to 255	unsigned char
INT	16-bit signed integer, representing integer values from –32768 to +32767	signed short int
WORD	16-bit unsigned integer, representing integer values from 0 to +65535	unsigned short int
LONG	32-bit signed integer, representing integer values from –2,147,483,648 to +2,147,483,647	signed long int
DWORD	32-bit unsigned integer, representing integer values from 0 to +4,294,967,295	unsigned long int

1 Scope

This standard defines a file format for interchanging audio data between compliant equipment. It is primarily intended for audio applications in professional recording, production, post production, and archiving.

It is derived from the EBU Broadcast Wave Format but is also compatible with variant specifications including ITU-R BR.1352-2-2002 and the Japan Post Production Association's BWF-J.

An optional extended format, BWF-E, supports 64-bit addressing to permit file sizes greater than 4 GBytes. Provision is made to support international character sets for human-readable information.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

SMPTE 330M-2000; *SMPTE standard for television - Unique Material Identifier (UMID),* Society of Motion Picture and Television Engineers, White Plains, NY., US.

ISO/IEC 646:1991; *Information technology - ISO-7-bit coded character set for information interchange.* International Standards Organisation, Geneva, Switzerland

ISO 8601; *Data elements and interchange formats - Information interchange - Representation of dates and times* International Standards Organisation, Geneva, Switzerland

ISO/IEC 10646:2012; Information technology - Universal Multiple-Octet Coded Character Set (UCS)

IETF RFC 3629; UTF-8, a transformation format of ISO 10646

3 Definitions and abbreviations

For the purposes of this document, the following terms and definitions apply.

3.1
RIFF
resource interchange file format, a file representation upon which the Wave file format is based

3.2
chunk
data package within RIFF files containing related data

3.3
ASCII
7-bit character code compliant with ISO/IEC 646

3.4
Wave
Audio file format based on the RIFF file structure

3.5
EBU
European Broadcasting Union