

STANDARDS AND INFORMATION DOCUMENTS

AES55-2012
revision of AES55-2007
reaffirmed 2017



AES standard for digital audio engineering - Carriage of MPEG Surround in an AES3 bitstream

Users of this standard are encouraged to determine if they are using the latest printing incorporating all current amendments and editorial corrections. Information on the latest status, edition, and printing of a standard can be found at:
<http://www.aes.org/standards>

AUDIO ENGINEERING SOCIETY, INC.
551 Fifth Avenue, New York, New York, 10176, US.

Document preview:
for full document, go to
www.aes.org/publications/standards

AES standard for digital audio engineering - Carriage of MPEG Surround in an AES3 bitstream

Published by

Audio Engineering Society, Inc.

Copyright © 2007, 2012, 2017 by the Audio Engineering Society

Abstract

MPEG-D is an ISO/IEC standard describing MPEG Surround that extends mono or stereo audio towards multiple channels. The mono or stereo audio channels represent a downmix of the original multi-channel audio that is generated by the MPEG Surround encoder. In addition the MPEG Surround encoder generates spatial side information (MPEG Surround data). An MPEG Surround decoder is able to combine this information with the downmix to result in a multi-channel audio signal. In this way backward compatibility to mono and stereo systems is achieved.

More recently, MPEG-D has been revised to include MPEG SAOC (Spatial Audio Object Coding) that uses the same method to convey the related side information over PCM.

This standard specifies how MPEG Surround or MPEG SAOC shall be carried within an AES3 bitstream where the downmix channels remain in the linear PCM domain and the MPEG Surround or MPEG SAOC data is embedded into the least-significant bits of the PCM audio data.

An AES standard implies a consensus of those directly and materially affected by its scope and provisions and is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an AES standard does not in any respect preclude anyone, whether or not he or she has approved the document, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in agreement with the standard. Prior to approval, all parties were provided opportunities to comment or object to any provision. Attention is drawn to the possibility that some of the elements of this AES standard or information document may be the subject of patent rights. AES shall not be held responsible for identifying any or all such patents. Approval does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the standards document. This document is subject to periodic review and users are cautioned to obtain the latest edition. Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Contents

Introduction	4
1 Scope	4
2 Normative references	4
3 Abbreviations	5
4 MPEG Surround in an AES3 bitstream	6
4.1 Embedding buried data	6
4.2 Defining audio word length	6
4.3 Indicating hidden information	6
Annex A (normative) MPEG Surround over PCM	7
A.1 Format of MPEG Surround and MPEG SAOC buried-data frames	7
A.2 MPEG Surround and MPEG SAOC detection	7
A.2.1 General	7
A.2.2 Positive indication of hidden data and audio word length	7
A.2.3 Positive indication of hidden data, default audio word length	8
A.2.4 No indication of hidden data	8
Annex B Bibliography	9

Foreword

This foreword is not part of the *AES standard for digital audio engineering - Carriage of MPEG Surround in an AES3 bitstream*, AES55-2007.

This document was developed under project AES-X159. The members of the writing group that developed this document in draft are: R. Caine, C. Cellier, J. Grant, J. Herre, K. Kjörling, W. Oomen, E. Schuijers, J. Woodgate, M. Yonge.

J. Grant
Chair, working group SC-02-02

Foreword to 2012 revision

This revision extends the previous edition to include MPEG Spatial Audio Object Coding (SAOC), and was principally contributed by A. Borsum.

J. Grant
Chair, working group SC-02-02

Note on normative language

In AES standards documents, sentences containing the word “shall” are requirements for compliance with the document. Sentences containing the verb “should” are strong suggestions (recommendations). Sentences giving permission use the verb “may”. Sentences expressing a possibility use the verb “can”.

AES standard for digital audio engineering - Carriage of MPEG Surround in an AES3 bitstream

0 Introduction

MPEG Surround is an ISO/IEC standard to extend mono or stereo audio towards multiple channels. The mono or stereo audio channels represent a downmix of the original multi-channel audio that is generated by the MPEG Surround encoder. In addition the MPEG Surround encoder generates spatial side information (MPEG Surround data). An MPEG Surround decoder is able to combine this information with the downmix to result in a multi-channel audio signal. In this way backward compatibility to conventional mono and stereo systems is achieved.

MPEG Spatial Audio Object Coding (SAOC) is an ISO/IEC standard to encode, transmit, and interactively render multiple audio objects for playback with various kinds of channel configurations. Side information is conveyed alongside a compatible mix-down of the incoming audio objects which can be rendered by an MPEG SAOC decoder for different reproduction scenarios. As for MPEG Surround, MPEG SAOC provides backward compatibility to mono or stereo systems.

The format of the AES3 interface consists of a sequence of AES3 subframes. Each AES3 subframe is normally used to carry one linear PCM sample. MPEG Surround or SAOC data can be conveyed as buried data over traditional PCM audio channels by adding a noise-like signal with specific characteristics to the less-significant bits of the PCM data. By embedding buried data into the PCM samples, the AES3 format itself is not affected, except for a mechanism to signal the presence of data hidden in the PCM samples using the channel status.

This noise-like signal, which actually is a randomized version of the embedded data, can be rendered inaudible by employing subtractive dithered noise-shaping controlled by the masked threshold.

1 Scope

This standard specifies a means of transport of an MPEG Surround and MPEG SAOC bitstreams over an AES3-compliant transport. The transport method is intended to be compatible with IEC 60958-compliant transport. The standard does not consider compression or processing algorithms associated with MPEG Surround or MPEG SAOC.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60958-1 Ed.3.0: 2008 *Digital audio Interface – Part 1: General*, International Electrotechnical Commission, Geneva, Switzerland. www.iec.ch

AES3-2009, *AES standard for digital audio – Digital input-output interfacing – Serial transmission format for two channel linearly represented digital audio data*, Audio Engineering Society, New York, US. www.aes.org