

STANDARDS AND INFORMATION DOCUMENTS

**AES18-1998
stabilized 2019**



AES recommended practice for digital audio engineering — Format for the user data channel of the AES digital audio interface

Users of this standard are encouraged to determine if they are using the latest printing incorporating all current amendments and editorial corrections. Information on the latest status, edition, and printing of a standard can be found at:
<http://www.aes.org/standards>

AUDIO ENGINEERING SOCIETY, INC.
551 Fifth Avenue, Room 1225, New York, NY 10176, US.



The AES Standards Committee is the organization responsible for the standards program of the Audio Engineering Society. It publishes technical standards, information documents and technical reports. Working groups and task groups with a fully international membership are engaged in writing standards covering fields that include topics of specific relevance to professional audio. Membership of any AES standards working group is open to all individuals who are materially and directly affected by the documents that may be issued under the scope of that working group.

Complete information, including working group scopes and project status is available at <http://www.aes.org/standards>. Enquiries may be addressed to standards@aes.org

The AES Standards Committee is supported in part by those listed below who, as Standards Sustainers, make significant financial contribution to its operation.



audio-technica



CLAIR



WEISS



METRIC HALO



This list is current as of 2018/9/01

**AES recommended practice for digital audio
engineering —
Format for the user data channel of the
AES digital audio interface**

Published by

Audio Engineering Society, Inc.

Copyright ©1996 by the Audio Engineering Society

Abstract

This document describes a method of formatting the user data channels provided within the digital audio serial interface format (AES3). The transmission format is an adaptation of the packet-based high-level data link control (HDLC) communications protocol and provides for the transmission of ancillary data that may or may not be time related to the audio signal. The data rate is constant within a range of ± 12.5 percent of a sampling frequency of 48 kHz. The standard also provides a data priority and management strategy to ensure that adequate capacity is available for downstream data insertion.

An AES standard implies a consensus of those directly and materially affected by its scope and provisions and is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an AES standard does not in any respect preclude anyone, whether or not he or she has approved the document, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standard. This document is subject to periodic review and users are cautioned to obtain the latest edition.

Document preview:
for full document, go to
www.aes.org/publications/standards

Contents

Foreword	3
1 Scope.....	4
2 Normative references	4
3 Definitions.....	4
4 General description	5
4.1 Messages	5
4.2 Transport system.....	6
4.3 Packets.....	6
4.4 Features.....	6
5 Data formatting.....	7
5.1 Application level.....	7
5.2 Transport system.....	7
6 Channel management.....	12
6.1 Channel formatting.....	12
6.2 Channel description.....	13
6.3 Data insertion (see annex A).....	15
7 Addressing of applications.....	18
7.1 Introduction	18
7.2 Classes of application.....	18
7.3 Applications	18
7.4 Message exchange.....	19
7.5 Addressing.....	19
7.6 Assignment of reserved bits	20
Annex A (Informative) New packets.....	44
Annex B (Informative) Code tables.....	45
Annex C Bibliography	46

Foreword

[This foreword is not a part of *AES Recommended practice for digital audio engineering Format for the user data channel of the AES digital audio interface*, AES18-1996.]

This document is a revision of AES18-1992. It is a companion document to the AES digital audio interface specification AES3, *AES Recommended practice for digital audio engineering Serial transmission format for two-channel linearly represented digital audio data* and its revisions. It is the result of a desire by users of the interface to have a recommended format for the user data channel provided by the user bit.

In this edition, an amendment has been added to provide recommendations for coding to be used in complying with AES18 and to complete the subclauses therein. The coding is presented in an added clause 7 and an added annex B. An added annex C provides informative references for the coding. The coding has been developed in cooperation with the European Broadcasting Union.

The requirement was for a system that is flexible and independent of the user application, and that can carry message data related in time to the audio data, as well as information, such as text, that may be unrelated to the audio data. A further requirement was for a format that treats the user data channel as a transparent carrier at sampling frequencies in the range of 48 kHz \pm 12.5 percent such that a constant data rate is achieved. The system specified is based on a widely used packet communication protocol, high-level data link control (HDLC) (ISO Publication 3309), which is standardized in the information technology industry. The HDLC protocol has been adapted for unidirectional transmission and to permit the accurate transmission of time-dependent information, but the HDLC integrated circuits, which are readily available from several manufacturers, are still able to be used. It is therefore expected that this transmission format will be easy to implement without recourse to special hardware and will, as a result, be included as a matter of routine in commercial interface equipment.

This document results from the work of the Working Group SC-02-04 Signal Labeling and Ancillary Data, established by SC-02 Subcommittee on Digital Audio of the AES Standards Committee, in close collaboration with the European Broadcasting Union (EBU).

Experimental and prototype equipment was designed and built by A. Komly and A. Viallevieille to prove and test the system during development of the specification. Input documents were provided by R. Lagadec, G. McNally, J. Wilkinson, A. Komly, A. Weisser, A. Viallevieille, and J. P. Nunn.

The following additional individuals participated in the preparation of the document: B. Blüthgen, R. Caine, R. Finger, W. Foster, N. Gilchrist, A. Griffiths, R. Hankinson, T. Holman, Y. Ishida, A. Komly, R. Lagadec, P. Lidbetter, S. Lyman, G. McNally, L. Moller, D. Queen, C. Sanchez, W. T. Shelton, A. Viallevieille, A. Weisser, and J. Wilkinson. In addition, R. Chalmers participated in the preparation of the revision.

J. P. NUNN, *Chairman*

SC-02-04 Working Group Signal Labeling and Ancillary Data
1996-07

Corrigendum 2005-05-12

In table 7, message address extension byte 2, units previously shown as “ft/s” have been corrected to read “frames/s”

Note on normative language

In AES standards documents, sentences containing the word “shall” are requirements for compliance with the document. Sentences containing the verb “should” are strong suggestions (recommendations). Sentences giving permission use the verb “may”. Sentences expressing a possibility use the verb “can”.

Document preview:
for full document, go to
www.aes.org/publications/standards

AES recommended practice for digital audio engineering – Format for the user data channel of the AES digital audio interface

1 Scope

This document specifies a recommended method of formatting the user bit of each channel of the AES digital audio interface (AES3, *AES Recommended practice for digital audio engineering – Serial transmission format for two-channel linearly represented digital audio data*). Each user data channel so formed is independent of the user application and is primarily intended for the transmission of data associated with the audio signal, although data unrelated to the audio signal may also be transmitted. There is no restriction on the length of messages that may be transmitted in the user data channel. The format treats the user data channel as a transparent carrier at sampling frequencies in the range of 42 kHz to 54 kHz, that is, $48 \text{ kHz} \pm 12.5 \text{ percent}$. There is no theoretical upper limit, but if sample rate conversion to a sampling frequency below this range is performed, data management is to be used to avoid loss of vital data.

The document describes the method of formatting user information into packets, together with the rules for data insertion into the multiplex and for data management. The purpose and the content of the user information for particular applications are outside the scope of this document.

This document describes a practice for professional applications and is not intended to encompass applications related to consumer versions of the digital audio interface.

2 Normative references

The following standards contain provisions that, through reference in this text, constitute provisions of this document. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this document are encouraged to investigate the possibility of applying the most recent editions of the indicated standards.

1) AES3-1992, *AES Recommended practice for digital audio engineering – Serial transmission format for two-channel linearly represented digital audio data*. New York: Audio Engineering Society, 1992.

2) ISO 3309, *Information processing systems Data communications High-level data link control procedures Frame structure*. Geneva, Switzerland: International Organization for Standardization, 1984.

3 Definitions

3.1 transport system: Method by which messages are carried between source and destination of the application.

3.2 address: Identification of either the destination hardware or the application. It can be combined with an address extension.

3.3 address extension: Part of the address that extends the range of destination hardware or applications that may be addressed.

3.4 block: Repetitive structure chosen for the transport system by the user.