

# STANDARDS AND INFORMATION DOCUMENTS

AES41-2-2012  
rev. AES41-2009  
reaffirmed 2022



**STANDARDS**

## **AES standard for digital audio - Audio-embedded metadata - Part 2: MPEG-1 Layer II or MPEG-2 LSF Layer II**

Users of this standard are encouraged to determine if they are using the latest printing incorporating all current amendments and editorial corrections. Information on the latest status, edition, and printing of a standard can be found at:  
<http://www.aes.org/standards>

**AUDIO ENGINEERING SOCIETY, INC.**  
132 East 43rd St., Suite 405, New York, NY 10017, US.



The AES Standards Committee is the organization responsible for the standards program of the Audio Engineering Society. It publishes technical standards, information documents and technical reports. Working groups and task groups with a fully international membership are engaged in writing standards covering fields that include topics of specific relevance to professional audio. Membership of any AES standards working group is open to all individuals who are materially and directly affected by the documents that may be issued under the scope of that working group.

Complete information, including working group scopes and project status is available at <http://www.aes.org/standards>. Enquiries may be addressed to [standards@aes.org](mailto:standards@aes.org)

## STANDARDS

The AES Standards Committee is supported in part by those listed below who, as Standards Sustainers, make significant financial contribution to its operation.



audio-technica



CLAIR



WEISS



METRIC HALO



This list is current as of 2018/9/01

# **AES standard for digital audio - Audio-embedded metadata - Part 2: MPEG-1 Layer II or MPEG-2 LSF Layer II**

Published by

**Audio Engineering Society, Inc.**

Copyright © 2009, 2012, 2017 by the Audio Engineering Society

## **Abstract**

AES41 provides for the carriage of audio metadata by embedding it in the audio samples themselves. This tightly associates the metadata with the audio, yet makes it fragile so that changes to the audio will invalidate the metadata. Several metadata sets have been defined, covering applications such as cascaded compression (bit rate reduction), and loudness control.

This part describes the format for the data to be transmitted with audio decoded from MPEG-1 Layer II or MPEG-2 LSF Layer II encoding. The data may be used to aid a subsequent re-encoding process. A method of carrying this data is described in Part 1 of this Standard.

An AES standard implies a consensus of those directly and materially affected by its scope and provisions and is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an AES standard does not in any respect preclude anyone, whether or not he or she has approved the document, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in agreement with the standard. Prior to approval, all parties were provided opportunities to comment or object to any provision. Attention is drawn to the possibility that some of the elements of this AES standard or information document may be the subject of patent rights. AES shall not be held responsible for identifying any or all such patents. Approval does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the standards document. Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation. This document is subject to periodic review and users are cautioned to obtain the latest edition.

**Contents**

<b>0 Introduction</b> .....	<b>4</b>
0.1 Rationale for part 2 of this standard.....	4
0.2 Patents.....	4
<b>1 Scope</b> .....	<b>5</b>
<b>2 Normative references</b> .....	<b>5</b>
<b>3 Definitions, symbols, and abbreviations</b> .....	<b>5</b>
3.1 Definitions.....	5
3.2 Symbols.....	7
3.3 Abbreviations.....	8
<b>4 Information for transparency</b> .....	<b>8</b>
<b>5 Recoding_data for MPEG-1, or MPEG-2 low sampling frequency</b> .....	<b>9</b>
5.1 AES41 metadata type.....	9
5.2 Syntax.....	9
5.3 Semantics.....	9
<b>6 Sample alignment of audio coder control data with respect to decoded-audio signal</b> .....	<b>10</b>
6.1 General.....	10
6.2 MPEG-1 Layer II or MPEG-2 Layer II.....	10
<b>Annex A (informative) Using the audio coder control data</b> .....	<b>11</b>
A.1 Derivation of MPEG scale-factor select information in the encoder.....	11
A.2 The introduced time-offset field.....	11
A.3 Graphics of audio coder control data bit-stream syntax.....	12
<b>Annex B (informative) Data alignment to decoded audio samples</b> .....	<b>14</b>
B.1 Synthesis filter bank and audio coder control data generating decoder.....	14
B.2 Analysis filter bank and audio coder control data assisted encoder.....	15
<b>Annex C (informative) Transmitting MPEG 2 LSF control data</b> .....	<b>16</b>

## **Foreword**

This foreword is not part of the *AES41-2-2012 AES standard for digital audio - Audio-embedded metadata - Part 2: MPEG-1 Layer II or MPEG-2 LSF Layer II*.

This document describes a set of data that may be conveyed according to the method described in Part 1 of this Standard. It is one part of a multi-part revision of AES41-2009.

Digital compression is used for a significant amount of program acquisition, for program production and storage, and for distribution and broadcasting.

Compression systems add impairments to sound. The audibility of these impairments depends on the degree of compression and the techniques used. It has been proved that re-encoding with minimal further impairment can be achieved by using information describing the previous encoding process. The information that is preserved varies according to the encoding scheme that has been used. For example, for transparent cascaded coding of MPEG-1 Layer II or MPEG-2 Layer II audio, the information required by the downstream encoder includes:

- . the positions of the frame boundaries;
- . the bit rate of the compressed bit stream before decoding;
- . the coding mode (monophonic, joint stereo, and so on);
- . the bit allocation for each sub-band within a frame;
- . the scale factors for each sub-band within each sub-block of a frame.

In order to help with the process of editing decoded audio, it is useful to send additional coding-decision data to describe any timing offset that may be introduced by editing only at points corresponding to block boundaries (for example, 24-ms boundaries for MPEG-1 Layer II at 48 kHz). These data are particularly relevant for editing sound associated with co-timed video. The bit rate of these additional data is less than 30 kbit/s. A cyclic-redundancy check word must be appended to frames of data to provide a means to detect errors in the data.

This data signal can be used by a downstream encoder to guide its coding decisions. For example, if the audio signal is changed in any way (as it would by mixing it with another signal) then it could be inappropriate for the downstream encoder to re-use any previous coding decisions. However, in such a case, when a suitable transport mechanism is used, the coding-decision data would be corrupted so the coder could detect that the data are no longer valid.

This specification describes in detail the content of the coding-decision information, such as MPEG-header information, bit allocations, and scale factors, plus its representation in terms of the number, order, and meaning of its bits. A mechanism by which these data can be conveyed in a pulse-code-modulation audio signal is also described. The mechanism modifies one of the least significant bits of the audio word to signal the data. The precise time relationship of the data to the audio is also defined.

The draft of this document was developed by a writing group whose primary author was Andrew Mason.

John Grant  
Chair, working group SC-02-02  
2012-03

### **Note on normative language**

In AES standards documents, sentences containing the word “shall” are requirements for compliance with the document. Sentences containing the verb “should” are strong suggestions (recommendations). Sentences giving permission use the verb “may”. Sentences expressing a possibility use the verb “can”.

# **AES standard for digital audio - Audio-embedded metadata - Part 2: MPEG-1 Layer II or MPEG-2 LSF Layer II**

## **0 Introduction**

AES41 provides for the carriage of audio metadata by embedding it in the audio samples themselves. This tightly associates the metadata with the audio, yet makes it fragile so that changes to the audio will invalidate the metadata. Several metadata sets have been defined, covering applications such as cascaded compression (bit rate reduction), and loudness control.

This part describes the format for the data to be transmitted with audio decoded from MPEG-1 Layer II or MPEG-2 LSF Layer II encoding. The data may be used to aid a subsequent re-encoding process. This part should be read in conjunction with part 1.

### **0.1 Rationale for part 2 of this standard**

Digital compression techniques allow the use of lower bandwidth channels and less storage space or, conversely, allow faster transmission and the storage of more program material. Digital compression will be used for a significant amount of program acquisition, for program production and storage, and for distribution and broadcasting.

Compression systems add impairments to sound. The audibility of these impairments depends on the degree of compression and the techniques used.

It has been proved that re-encoding with minimal impairment can be achieved by using information describing the previous encoding process. The information that is preserved varies according to the encoding scheme that has been used, but might include framing and quantization resolution data.

### **0.2 Patents**

The Audio Engineering Society draws attention to the fact that it is claimed that compliance with this AES standard may involve the use of an application for patents concerning "Lip sync" and "Lip-sync with sub-frame error feedback."

The AES holds no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured the AES that it is willing to negotiate licenses under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is archived with the AES.

Information may be obtained from

British Broadcasting Corporation  
Attention of Daniel Pike  
BBC Research and Development  
Centre House  
56 Wood Lane  
London, W12 7SB  
UK

Attention is drawn to the possibility that some of the elements of this AES standard may be the subject of patent rights other than those identified herein. AES shall not be held responsible for identifying any or all such patent rights.

## **1 Scope**

This document describes a format for the data to be transmitted to identify MPEG-1 Layer II and MPEG-2 LSF Layer II audio bit-rate reduction. This part assumes that the transmission mechanism according to part 1 of this Standard is used.

## **2 Normative references**

The following standards contain provisions that, through reference in this text, constitute provisions of this document. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this document are encouraged to investigate the possibility of applying the most recent editions of the indicated standards.

**AES41-1-xxxx**, *AES standard for digital audio - Audio-embedded metadata - Part 1: General*, Audio Engineering Society, New York, NY., US.

**ISO/IEC 11172-3** (1993-08), *Information technology - Coding of moving pictures and associated audio for digital storage media at up to about 1,5 Mbit/s - Part 3: Audio*. International Electrotechnical Commission, Geneva, Switzerland.

**ISO/IEC 13818-3** (1998-05), *Information technology - Generic coding of moving picture and associated audio information - Part 3: Audio*. International Electrotechnical Commission, Geneva, Switzerland.

## **3 Definitions, symbols, and abbreviations**

### **3.1 Definitions**

#### **3.1.1**

##### **analysis filter bank**

filter bank in the encoder that transforms a broadband pulse-code-modulation (PCM) audio signal into a set of subsampled sub-band samples

#### **3.1.2**

##### **channel**

means of carrying an audio signal (for example, a sequence of data forming part of a bit stream)

#### **3.1.3**

##### **coded-audio bit stream**

coded representation of an audio signal

#### **3.1.4**

##### **compression**

reduction in the number of bits used to represent an item of data

#### **3.1.5**

##### **CRC**

cyclic redundancy check

#### **3.1.6**

##### **dual-channel mode**

mode where two audio channels with independent program contents (for example, bilingual) are encoded within one bit stream

NOTE The coding process is the same as for the stereo mode.